

# **ASBU ELEMENTS**

ASUR COMI COMS CSEP

☑ Functional Description ☑ Enal

☑ Enablers ☑ Deployment Applicability

**☑** Performance Impact Assessment

### ASUR -

ASUR-B0/1 Automatic Dependent Surveillance – Broadcast Technology (ADS-B)

Sixth edition of the GANP ?

Main Purpose To support the provision of Air Traffic Services and operational applications at reduced cost and increased surveillance coverage.

New Capabilities ADS-B provides precise position/velocity information in all airspace (accuracy not range-dependent as with radar). It also provides aircraft call sign and precise position/velocity information to nearby aircraft with ADS-B-In receivers.

ADS-B can also support State aircraft airspace access, however it should, when possible, leverage benefits from dual-use of State aircraft capabilities to reduce cost and technical impact.

Description ADS-B provides an aircraft's identification, position, altitude, velocity, and other information to any receiver (airborne or ground) within range. The broadcasted aircraft position/velocity is normally

receiver (airborne or ground) within range. The broadcasted aircraft position/velocity is normally based on the global navigation satellite system (GNSS) and transmitted at least once per second.

Maturity Level Ready for implementation

Human Factor
Considerations

PLANNING LAYERS ②

Tactical-During ops

OPERATIONS 
Taxi-out Departure En-route Arrival Taxi-in

DEPENDENCIES AND RELATIONS		TIONS 2
	Type of Dependencies	ASBU Element
	Relation-operational need	NAVS-B0/3 - Aircraft Based Augmentation Systems (ABAS)
	Relation-benefit	NAVS-B0/2 - Satellite Based Augmentation Systems (SBAS)

ENABLER	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Ground system infrastructur e	Surveillance	ADS-B ground stations	ADS-B ground stations receive information from aircraft and transmit it to one or more Service Delivery Points Reference material: Technical standards and guidance material: ICAO Annex 10 Volume IV Chapter 2,3 and 5 ICAO Doc. 9871 Technical Provisions for Mode S Services and Extended Squitter RTCA/EUROCAE MOPS: DO-260/ED-102, DO-260A, or DO-260B/ED-102A EUROCAE ED-129, ED-129A or ED-129B ICAO Doc. 9924 Aeronautical Surveillance Manual	ANSP	2008
Ground system infrastructur e	Surveillance	*Service Delivery Point(s) for ADS- B information	Service Delivery Point(s) receive ADS-B information provides it to ATC automation for processing and display to controller Reference material: Guidance material: ICAO Doc. 9924 Aeronautical Surveillance Manual	ANSP	2008
Ground system infrastructur e	Technical systems	HMI that supports controller awareness	Human Machine Interface (HMI) of the Air Traffic Controller Working Position (ATCo CWP) Reference: Guidance material: ICAO Doc. 9924 Aeronautical Surveillance Manual	ANSP	2008
Airborne system capability	Surveillance	SSR Mode S transponder with extended squitter version 0, version 1 and version 2	Reference: Technical standards and guidance material: ICAO Annex 10 Volume IV Chapter 2,3 and 5 ICAO Doc. 9871 Technical Provisions for Mode S Services and Extended Squitter RTCA/EUROCAE MOPS: DO-260/ED- 102, DO-260A, or DO-260B/ED-102A ICAO Doc. 9924 Aeronautical Surveillance Manual	Aircraft manufacturer  Aircraft operator	2008
Training	-	Training requirements ADS-B implementation	Depending on the ANSP implementation, some controller training on new symbology may be required. If phraseology is changed by an ANSP, then controller and pilot training on the new phraseology is required. If new ANSP equipment is installed, then training for maintenance personnel may be required (see ICAO Doc 8071).	ANSP	2008

Airborne system capability Navigation

**Basic Aviation** GNSS receiver with RAIM

Position source. Basic Aviation GNSS receiver with RAIM. Such a receiver must comply with the technical performance requirements of either [E]TSO-C129, or [E]TSO-C196, or [E]TSO-C145/-C146. (Note that the US/Europe and equivalent ADS-B mandates require more - see FAA AC 20-165 or EASA CS-ACNS).

Aircraft manufacturer

2008

Aircraft operator

ASUR-B0/2

Multilateration cooperative surveillance systems (MLAT)

Technology

☐ Sixth edition of the GANP ②

Main Purpose To provide an alternative to radar surveillance by using available aircraft transponders.

New Capabilities MLAT allows cooperative surveillance in rough terrain such as in mountainous regions or on airport surfaces where surveillance systems requiring a rotating radar dish had performance difficulties. It may also be integrated with ADS-B ground stations to provide a surveillance capability that is more resilient to GNSS function failure.

Description ? MLAT is a new technique providing independent cooperative surveillance. The MLAT system interrogates an aircraft and the transponder reply is received by multiple receivers located in different places. The reply's times of arrival difference at the receivers allows the position of the source of signals to be determined, with an accuracy that is dependent on the number of receivers and their location relative to the aircraft. MLAT systems do not require a rotating radar dish and were initially deployed on airports to provide surface surveillance of aircraft. The technique is now used to provide surveillance over wide area (wide area MLAT system - WAM), sometimes in conjunction with ADS-B. MLAT requires more ground stations than ADS-B, but has the early implementation advantage of

Maturity Level ? Ready for implementation

using existing aircraft transponders.

**Human Factor** Considerations

PLANNING LAYERS ?

Tactical-During ops

**OPERATIONS 2** 

Taxi-out Departure En-route Arrival Taxi-in

DEPENDENCIES AND RELATIONS ?

There are currently no dependencies.

**ENABLERS** 

Enabler **Stakeholders Enabler Type** Enabler Name **Description / References** Year

Category

Ground	Survoillance	MI AT ground	MI AT ground stations interrogate aircraft	ANICD	2008
Ground system infrastructur e	Surveillance	MLAT ground stations	MLAT ground stations interrogate aircraft transponders and receive/process transponder replies to determine aircraft position; this information is then transmitted to Service Delivery Point(s) Reference material: Technical standards and guidance material: ICAO Annex 10 Volume IV Chapters 2,3,5 and 6. ICAO Doc 9871 Technical Provisions for Mode S Services and Extended Squitter RTCA/EUROCAE MOPS: DO-181D/ED-73C or subsequent versions ICAO Doc. 9924 Aeronautical Surveillance Manual	ANSP	2008
Airborne system capability	Surveillance	SSR Mode A, C and S transponders	References: Technical standards and guidance material: ICAO Annex 10 Volume IV Chapter 2,3 and 5 ICAO Doc. 9871 Technical Provisions for Mode S Services and Extended Squitter RTCA/EUROCAE MOPS: DO-181D/ED- 73C or subsequent versions ICAO Doc. 9924 Aeronautical Surveillance Manual	Aircraft manufacturer Aircraft operator	2008
Ground system infrastructur e	Surveillance	Service Delivery Point (s) for MLAT information	Service Delivery Points(s) receive MLAT information and provide it to ATC automation for display to controller Reference: Guidance material: ICAO Doc. 9924 Aeronautical Surveillance Manual	ANSP	2008
Training	-	Training requirements MLAT implementation	If new ANSP equipment is installed, then training for maintenance personnel may be required (see Doc 8071).	ANSP	2008

ASUR-B0/3	Cooperative Surveillance Radar Downlink of Technology Aircraft Parameters (SSR-DAPS)
☐ Sixth edition of the	e GANP 2
Main Purpose    Output  Description:	To obtain additional information from an aircraft transponder in support of the provision of Air Traffic Services.
New Capabilities 2	SSR-DAPS enables ATM systems to obtain additional information from an aircraft transponder, via interrogation by a cooperative surveillance system (Mode S radar or MLAT). This additional information can be used to increase controller awareness and reduce the volume of air-ground voice communications, and/or to improve the performance of tracking systems or safety net systems such as STCA and MSAW.

Description 2

Downlink of Aircraft Parameters (DAPS) includes both Controller Access Parameters (CAPs) and System Access Parameters (SAPs). Possible CAPs include Magnetic Heading, Indicated Airspeed / Mach Number, Barometric rate of climb/descent, and Selected Altitude (which can also be consider a SAP). SAPs include Roll Angle, Track Angle Rate, True Track Angle, and Barometric Pressure Setting.

Maturity Level ?

Ready for implementation

Human Factor Considerations

PLANNING LAYERS ?

Tactical-During ops



### DEPENDENCIES AND RELATIONS ②

There are currently no dependencies.

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Airborne	Surveillance	SSR Mode A, C	References: Technical standards and	Aircraft manufacturer	2008
system capability		and S transponders	guidance material: ICAO Annex 10 Volume IV Chapter 2,3 and 5 ICAO Doc.	Aircraft operator	
,			9871 Technical Provisions for Mode S		
			Services and Extended Squitter RTCA/EUROCAE MOPS: DO-181D/ED-		
			73C or subsequent versions ICAO Doc.		
			9924 Aeronautical Surveillance Manual		
Ground system	Surveillance	Mode S cooperative	Mode S cooperative surveillance system with DAPS capability interrogates aircraft	ANSP	2008
infrastructur		surveillance	transponders to retrieve data; this		
е		system	information is then provided to the ATC		
			automation system. Reference material: Technical standards and guidance		
			material: ICAO Annex 10 Volume IV		
			Chapter 2,3 and 5 ICAO Doc. 9871		
			Technical Provisions for Mode S Services and Extended Squitter: RTCA/EUROCAE		
			MOPS: DO-181D/ED-73C or subsequent		
			versions ICAO Doc. 9924 Aeronautical		
			Surveillance Manual		

Ground system infrastructur e	Technical systems	*HMI that supports controller awareness for CAPs and automation processing for SAPs	Reference: Guidance material: ICAO Doc 9924 Aeronautical Surveillance Manual	ANSP	2008
Training	-	Training requirements SSR-DAPS implementation	Depending on the ANSP implementation, some controller training on new symbology or alerts may be required. If phraseology is changed, or new phraseology is introduced by an ANSP, then controller and pilot training on the new phraseology is required. If new ANSP equipment is installed, then training for maintenance personnel may be required (see Doc 8071).	ANSP	2008

ASUR-B1/1 Reception of aircraft ADS-B signals from space Technology (SB ADS-B) ☐ Sixth edition of the GANP ② To provide surveillance coverage in locations where ground stations siting is not possible or not Main Purpose ? currently provided. New Capabilities SB ADS-B provides precise position/velocity information in airspace where it is not cost-effective or even feasible to place ground surveillance infrastructure. ADS-B provides an aircraft's identification, position, altitude, velocity, and other information to a Description ? receiver on an orbiting satellite. The broadcasted aircraft position/velocity is normally based on the global navigation satellite system (GNSS) and transmitted at least once per second. Aircraft ADS-B signals are received on one or more orbiting satellites, and this information is passed through a data network to a Service Delivery Point at an Air Traffic Service facility (or facilities). Maturity Level ? Ready for implementation **Human Factor** 

PLANNING LAYERS 2

Tactical-During ops

Considerations

OPERATIONS 

Departure En-route Arrival

### DEPENDENCIES AND RELATIONS 3


Type of Dependencies ASBU Element

Evolution ASUR-B0/1 - Automatic Dependent Surveillance – Broadcast (ADS-B)

Relation-operational need	NAVS-B0/3 - Aircraft Based Augmentation Systems (ABAS)
Relation-benefit	NAVS-B0/2 - Satellite Based Augmentation Systems (SBAS)

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Ground system infrastructur e	Technical systems	HMI that supports controller awareness	Human Machine Interface (HMI) of the Air Traffic Controller Working Position (ATCo CWP) Reference: Guidance material: ICAO Doc. 9924 Aeronautical Surveillance Manual	ANSP	2008
Airborne system capability	Surveillance	SSR Mode S transponder with extended squitter version 0, version 1 and version 2	Reference: Technical standards and guidance material: ICAO Annex 10 Volume IV Chapter 2,3 and 5 ICAO Doc. 9871 Technical Provisions for Mode S Services and Extended Squitter RTCA/EUROCAE MOPS: DO-260/ED- 102, DO-260A, or DO-260B/ED-102A ICAO Doc. 9924 Aeronautical Surveillance Manual	Aircraft manufacturer  Aircraft operator	2008
Ground system infrastructur e	Surveillance	*ADS-B receivers on orbiting satellites	ADS-B receivers on orbiting satellites receive information from aircraft and transfer this information to ground Service Delivery Point(s). Reference: Technical standards and guidance material: ICAO Annex 10 Volume IV Chapter 2,3 and 5 ICAO Doc. 9871 Technical Provisions for Mode S Services and Extended Squitter: RTCA/EUROCAE MOPS: DO-260/ED-102, DO-260A, or DO-260B/ED-102A EUROCAE ED-129A or ED-129B ICAO Doc. 9924 Aeronautical Surveillance Manual	ANSP	2015
Ground system infrastructur e	Surveillance	Service Delivery Point(s) for satellite ADS-B	Service Delivery Point(s) receive information and transfer it to ATC automation for processing and display to controller. Reference: Guidance material: ICAO Doc. 9924 Aeronautical Surveillance Manual	ANSP	2015

Training	-	Training requirements SB ADS-B	If this capability is used to apply new separation minima per PANS-ATM, controller training is required. Depending on the ANSP implementation, some controller training on new symbology may be required. If phraseology is changed by an ANSP, then controller and pilot training on the new phraseology is required. If new ANSP equipment is installed, then training for maintenance personnel may be required (see ICAO Doc 8071).	ANSP	2018
Airborne system capability	Navigation	Basic Aviation GNSS receiver with RAIM	Position source. Basic Aviation GNSS receiver with RAIM. Such a receiver must comply with the technical performance requirements of either [E]TSO-C129, or [E]TSO-C196, or [E]TSO-C145/-C146. (Note that the US/Europe and equivalent ADS-B mandates require more – see FAA AC 20-165 or EASA CS-ACNS).	Aircraft manufacturer Aircraft operator	2008



Tactical-During ops	Taxi-out	Departure	En-route	Arrival	Taxi-in	

Type of Dependencies  ASBU Element  Evolution  ASUR-B0/1 - Automatic Dependent Surveillance - Broadcast (ADS-B)
Evolution ASUR-B0/1 - Automatic Dependent Surveillance – Broadcast (ADS-B)
Evolution ASUR-B0/2 - Multilateration cooperative surveillance systems (MLAT)
Evolution ASUR-B0/3 - Cooperative Surveillance Radar Downlink of Aircraft Parameters (SSR-DAPS)
Evolution ASUR-B1/1 - Reception of aircraft ADS-B signals from space (SB ADS-B)
Relation-operational need NAVS-B0/3 - Aircraft Based Augmentation Systems (ABAS)
Relation-benefit NAVS-B0/2 - Satellite Based Augmentation Systems (SBAS)
Relation-benefit NAVS-B2/2 - Dual Frequency Multi Constellation (DF MC) SBAS
Relation-benefit NAVS-B2/3 - Dual Frequency Multi Constellation (DF MC) ABAS

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Ground system infrastructur e	Technical systems	HMI that supports controller awareness	Human Machine Interface (HMI) of the Air Traffic Controller Working Position (ATCo CWP) Reference: Guidance material: ICAO Doc. 9924 Aeronautical Surveillance Manual	ANSP	2008
Airborne system capability	Surveillance	SSR Mode S transponder with extended squitter version 3	Reference: Technical standards and guidance material: Future revision ICAO Annex 10 Volume IV Chapter 2,3 and 5 Future revision ICAO Doc. 9871 Technical Provisions for Mode S Services and Extended Squitter: RTCA/EUROCAE MOPS: DO-260C/ED-102C, DO-181F/ED-73F (TBC) Future revision ICAO Doc. 9924 Aeronautical Surveillance Manual	Aircraft manufacturer  Aircraft operator	2022

Ground system infrastr e		e ADS-B receivers and/or cooperative radars	ADS-B receivers and/or cooperative radars receive information from aircraft and transfer this information to Service Delivery Point(s). Reference material: Technical standards and guidance material: Future revision ICAO Annex 10 Volume IV Chapter 2,3 and 5 Future revision ICAO Doc. 9871 Technical	ANSP	2022
			Provisions for Mode S Services and Extended Squitter RTCA/EUROCAE MOPS: DO-260C/ED-102C, DO- 181F/ED-73F, ED-129B (or subsequent revision) Future revision ICAO Doc. 9924 Aeronautical Surveillance Manual		
Ground system infrastr e		Point(s) for ADS-B v3	Service Delivery Point(s) receive information and transfers it to ATC automation for processing and display to controller. Reference: Guidance material: Future revision of ICAO Doc. 9924 Aeronautical Surveillance Manual	ANSP	2022
Airborn	ne Navigation		Position source. Basic Aviation GNSS	Aircraft manufacturer	2008
system capabi		GNSS receiver with RAIM	receiver with RAIM. Such a receiver must comply with the technical performance	Aircraft operator	
			requirements of either [E]TSO-C129, or [E]TSO-C196, or [E]TSO-C145/-C146. (Note that the US/Europe and equivalent ADS-B mandates require more – see FAA AC 20-165 or EASA CS-ACNS).		

ASUR-B2/2	New community based surveillance system for Technology airborne aircraft (low and higher airspace)
Sixth edition of the	e GANP
Main Purpose ?	To support the provision of separation services by operators for aircraft operating at very low altitudes (<500 ft) and higher airspace.
New Capabilities 2	A community based network solution for surveillance at a lower lifecycle cost is provided using operator reported positions into that network to support conflict detection and resolution. It substitutes shared information for visual recognition of other aircraft.
Description ?	Within this timeframe, vehicle identities/positions/velocities may be shared using an aviation network. Information is provided to the ANSP on aircraft location to detect airspace infringement (low altitudes) and support operator to operator (even if provided by third party acting on the operators behalf) conflict management. It extends to higher airspace to support new entrants.
Maturity Level 2	Concept

### PLANNING LAYERS ?

Tactical-During ops

## OPERATIONS ②

Departure En-route Arrival

DEPENDENCIES AND RELATIONS 2				
Type of Dependencies	ASBU Element			
Relation-operational need	NAVS-B0/3 - Aircraft Based Augmentation Systems (ABAS)			
Relation-benefit	NAVS-B0/2 - Satellite Based Augmentation Systems (SBAS)			
Relation-benefit	NAVS-B2/2 - Dual Frequency Multi Constellation (DF MC) SBAS			
Relation-benefit	NAVS-B2/3 - Dual Frequency Multi Constellation (DF MC) ABAS			

ENABLER	2S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Ground system infrastructur e	Surveillance	"Public" network- based cooperative surveillance	"Public" network-based cooperative surveillance system collects, processes and shares "target" information; this information is then provided as needed to ANSP personnel.	ANSP	2024

ASUR-B3/1	New non-cooperative surveillance system for Technology airborne aircraft (medium altitudes)
☐ Sixth edition of the	e GANP 2
Main Purpose	To provide non-cooperative and independent surveillance system at a lower cost.
New Capabilities ?	Non-cooperative surveillance is provided at a lower lifecycle cost using multiple, networked receivers to detect aircraft-reflected RF signals originated from continuously transmitting non-aviation transmitters such as digital TV stations, FM radio stations, or cellphone towers.
Description ?	Information is provided to the ANSP on aircraft location to detect airspace infringement or to safely manage aircraft with surveillance equipment failure. A performance-based surveillance framework allows ANSPs to determine the most effective means of obtaining needed surveillance information. Within this timeframe, all aircraft identities/positions/velocities can be provided/shared by operators using an aviation network. Operators not receiving safety-of-life services can be surveilled using non-aviation spectrum.
Maturity Level	Concept

### PLANNING LAYERS ?

Tactical-During ops

### OPERATIONS ?

Departure En-route Arrival

### DEPENDENCIES AND RELATIONS 2

There are currently no dependencies.

ENABLER	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Ground system infrastructur e	Surveillance	*Non-cooperative surveillance system	Non-cooperative surveillance system observes RF reflections large enough to be declared as "targets"; this information is then provided to the ATC display (sometimes merged with data from cooperative surveillance systems).  Reference material: Future revision of ICAO Doc 9924 – Aeronautical Surveillance Manual	ANSP	2031

ASUR-B4/1	Further evolution of ADS-B and MLAT Technology				
☐ Sixth edition of th	e GANP 🕝				
Main Purpose ?	To support the provision of Air Traffic/MET Services and vehicle-to-vehicle applications in a full TBO environment and within a performance-based surveillance framework.				
New Capabilities    O	Additional aircraft/atmospheric information is provided in a performance-based surveillance context to resiliently support ANSP/MET and vehicle-to-vehicle applications in a full TBO environment.				
Description ?	This evolution will address TBO needs for surveillance information discovered in Block 2. A performance-based surveillance framework allows ANSPs to determine the most effective means of obtaining needed surveillance information.				
	Cooperative surveillance is expected to be the principal means of surveillance and is typically provided by ADS-B and MLAT systems; rotating radars will be replaced at end-of-life where appropriate. Within this timeframe, all aircraft identities/positions/velocities can be provided/shared by operators using internet. Operators not receiving safety-of-life services can be surveilled using non-aviation spectrum.				
Maturity Level 2	Concept				
Human Factor Considerations					

### 

Tactical-During ops

OPERATIONS 

Departure En-route Arrival

DEPENDENCIES AND RELATIONS    O				
Type of Dependencies	ASBU Element			
Evolution	ASUR-B2/1 - Evolution of ADS-B and Mode S			
Relation-operational need	NAVS-B2/2 - Dual Frequency Multi Constellation (DF MC) SBAS			
Relation-operational need	NAVS-B2/3 - Dual Frequency Multi Constellation (DF MC) ABAS			

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Ground system infrastructur e	Technical systems	HMI that supports controller awareness	Human Machine Interface (HMI) of the Air Traffic Controller Working Position (ATCo CWP) Reference: Guidance material: ICAO Doc. 9924 Aeronautical Surveillance Manual	ANSP	2008
Airborne system capability	Surveillance	SSR Mode S transponder with extended squitter version 4 (TBC)	Reference: Technical standards and guidance material: ICAO Annex 10 Volume IV Chapter 2,3 and 5 ICAO Doc. 9871 Technical Provisions for Mode S Services and Extended Squitter: RTCA/EUROCAE MOPS: DO-260D/ED- 102D (TBC) ICAO Doc. 9924 Aeronautical Surveillance Manual	Aircraft manufacturer Aircraft operator	2032
Ground system infrastructur e	Surveillance	ADS-B receivers and/or MLAT	ADS-B receivers and/or MLAT receive information from aircraft and transfer this information to Service Delivery Point(s) Reference material: Technical standards and guidance material: Future revision ICAO Annex 10 Volume IV Chapter 2,3 and 5 Future revision ICAO Doc. 9871 Technical Provisions for Mode S Services and Extended Squitter RTCA/EUROCAE MOPS: DO-260D/ED-102D (TBC); ED-129B (or subsequent revision) Future revision ICAO Doc. 9924 Aeronautical Surveillance Manual	ANSP	2032
Ground system infrastructur e	Surveillance	Service Delivery Point(s) for ADS- B v4	Service Delivery Point(s) receive information and transfers it to ATC automation for processing and display to controller. Reference: Guidance material: Future revision of ICAO Doc. 9924 Aeronautical Surveillance Manual	ANSP	2032

Airborne Navigation Basic Aviation system GNSS receiver capability with RAIM

Position source. Basic Aviation GNSS receiver with RAIM. Such a receiver must comply with the technical performance requirements of either [E]TSO-C129, or [E]TSO-C196, or [E]TSO-C145/-C146. (Note that the US/Europe and equivalent ADS-B mandates require more – see FAA AC 20-165 or EASA CS-ACNS).

Aircraft manufacturer 2008
Aircraft operator

### COMI \_\_\_\_

COMI-B0/1 Aircraft Communication Addressing and Technology
Reporting System (ACARS)

Sixth edition of the GANP 
Main Purpose The Aircraft Communications Addressing and Reporting System (ACARS) is a digital datalink

system for transmission of messages between aircraft and ground stations via VHF or satellites.

New Capabilities ACARS provides the network for the controller and pilot with the ability to exchange datalink messages and thus provides a backup to voice communications. It also provides for airline operational control messaging.

Description ACARS is a digital datalink network system which transmits and routes messages between aircraft and ground stations via VDL Mode 0/Mode2 radios or satellites.

Maturity Level **?** Ready for implementation

Human Factor
Considerations

### PLANNING LAYERS 2

Tactical-During ops

OPERATIONS 
Taxi-out Departure En-route Arrival Taxi-in

# Type of Dependencies ASBU Element Relation-technology option COMI-B0/3 - VHF Data Link (VDL) Mode 0/A Relation-technology option COMI-B0/4 - VHF Data Link (VDL) Mode 2 Basic Relation-technology option COMI-B0/5 - Satellite communications (SATCOM) Class C Data Relation-technology option COMI-B0/6 - High Frequency Data Link (HFDL) Relation-technology benefit COMI-B1/2 - VHF Data Link (VDL) Mode 2 Multi-Frequency

ENABLERS	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Protocols	Communicati on infrastructure	ACARS Protocols	AEEC 618- Air Ground Character- Oriented Protocol. (AEEC 620 Datalink Ground System Standard and Interface Specification) ARINC 622- ATS Datalink Applications over ACARS Air-Ground Network. AEEC 623- Character-Oriented Air Traffic Services. ARINC 633 is the air- ground definition for sending XML over ACARS	ANSP Aircraft manufacturer	2013
Airborne system capability	Communicati on infrastructure	ACARS Airborne Radio Transceiver	ACARS is a digital datalink system for transmission of short messages between aircraft and ground stations via airband radio or satellite. AEEC 618- Air Ground Character-Oriented Protocol. AEEC 620 Datalink Ground System Standard and Interface Specification ARINC 624 is a standard for aircraft onboard maintenance system	Aircraft manufacturer Aircraft operator	2013
Ground system infrastructure	Communicati on infrastructure	ACARS Ground Radio Transceiver	ACARS is a digital datalink system for transmission of short messages between aircraft and ground stations via airband radio or satellite. AEEC 618- Air Ground Character-Oriented Protocol. AEEC 620 Datalink Ground System Standard and Interface Specification	ANSP Ground systems supplier	2013
Space system infrastructure	Communicati on infrastructure	ACARS Space Radio Transceiver	Inmarsat Classic Aero Standard and Iridium Standard (includes a satellite data unit, a high power amplifier and an antenna with a steerable beam).	Satellite provider	2013

# COMI-B0/2 Aeronautical Telecommunication Network/Open Technology System Interconnection (ATN/OSI)

Main Purpose ATN/OSI provides a bit-oriented multi-layer protocol for exchanging ATS messages between the aircraft and ground system.

New Capabilities The ATN/OSI provides an alternative, dedicated ATS protocol for exchanging flight safety messages.

Description The ATN/OSI provides a dedicated ATS commulcations protocol for the usage of B1 data link applications (e.g. CPDLC and CM).

Maturity Level Ready for implementation

Human Factor Considerations

### PLANNING LAYERS 3

Tactical-During ops

### OPERATIONS ?

Taxi-out Departure En-route Arrival Taxi-in

## DEPENDENCIES AND RELATIONS

Type of Dependencies	ASBU Element
Relation-technology benefit	COMI-B1/2 - VHF Data Link (VDL) Mode 2 Multi-Frequency
Relation-technology benefit	COMI-B1/3 - SATCOM Class B Voice and Data
Relation-technology benefit	COMI-B3/1 - VHF Data Link (VDL) Mode-2 Connectionless
Relation-technology need	COMI-B0/4 - VHF Data Link (VDL) Mode 2 Basic

	EN	IΑI	31	FR	25
--	----	-----	----	----	----

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Protocols	Communicati on infrastructure	ATN/OSI protocol	ICAO Doc. 9880- Manual on Detailed Technical Specifications for the ATN/OSI.	ANSP	2013
Airborne system capability	Communicati on infrastructure	ATN/OSI Airborne Router	ICAO Doc. 9880 Manual on Detailed Technical Specifications for the ATN/OSI. Connectivity is to be accomplished over multiple subnetwork types. The ATN currently recognizes a limited set of subnetworks: SSR Mode Select (Mode S), Very High Frequency (VHF) Digital Link (VDL), Aeronautical Mobile Satellite Service (AMSS), Gatelink, and High Frequency (HF).	ANSP Aircraft manufacturer	2013
Ground system infrastructure	Communicati on infrastructure	ATN/OSI Ground Router	ICAO Doc. 9880- Manual on Detailed Technical Specifications for the ATN/OSI.	ANSP	2013

☐ Sixth edition of the GANP ②

VDL Mode 0/A is a data communications subnetwork that supports transmission of data link Main Purpose ? messages.

- New Capabilities Introduction of a datalink to support domestic data communications operations.
  - a supplement to voice communications
  - Exchanges aviation data (AOC, CPDLC and ADS)

Description ?

VDL Mode 0/A is a narrow-band transceiver operating in the VHF aviation protected spectrum band which will transmit data to and from the aircraft to support data communications. The VHF digital radio system is based on the double side band AM multi-shift keying modulation to transfer 2400 bps.

Maturity Level ?

Ready for implementation

**Human Factor** Considerations

### PLANNING LAYERS ②

Tactical-During ops

Sixth edition of the GANP ?



### DEPENDENCIES AND RELATIONS ②

There are currently no dependencies.

ENABLER	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Protocols	Communicati on infrastructure	"Plain Old" ACARS (POA) protocol	AEEC 758 - Communications  Management Unit ARINC 771 - Low-earth orbiting aviation satellite communication systems	ANSP Aircraft manufacturer	2013
Airborne system capability	Communicati on infrastructure	VDL Mode 0/A airborne Analog Radio	AEEC 618 - Air/ground character-oriented protocol specification	ANSP Aircraft manufacturer	2013
Ground system infrastructur e	Communicati on infrastructure	VDL Mode 0/A Ground Analog transceiver	Datalink Ground System Standards and Interface Specification (ARINC 620).  Defines the interfaces to the ACARS Ground System Operated by a Datalink Service Provider.	ANSP Ground systems supplier	2013

COMI-B0/4 VHF Data Link (VDL) Mode 2 Basic Technology Main Purpose **②** VDL Mode 2 Basic is a data communications subnetwork that supports transmission of data link messages. It provides higher performance than VDLM0/A.

New Capabilities • Provides an Increase in data capacity over VDL Mode O/A

- Exchanges aviation data (AOC, CPDLC and ADS)
- More efficient use of spectrum

VDL Mode 2 is narrow-band transceiver operating in the VHF aviation protected spectrum band, which will transmit data to support data communications between the aircraft and ground. It consists of a set of air-ground protocols that increase the data rate to 31.5 kbits.

Maturity Level Ready for implementation

Human Factor
Considerations



Tactical-During ops




### **DEPENDENCIES AND RELATIONS ?**

Type of Dependencies ASBU Element

Evolution COMFB0/3 - VHF Data Link (VDL) Mode 0/A

ENABLER	RS				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Protocols	Communicati on infrastructure	VDL-M2 operational Usage & Protocol	VDL-M2 is the primary VDL mode being implemented operationally to support Controller Pilot Data Link Communications. • ICAO Doc 9776 VDL2 Technical Manual • VHF air-ground Digital Link (VDL) Mode 2; Technical characteristics and methods of measurement for ground-based equipment ETSI EN 301 841-1 • RTCA DO 224 Minimum Aviation System Performance Standard) • ARINC 631 VHF Digital Link (VDL) Mode 2 implementation provisions	ANSP	2013
Airborne system capability	Communicati on infrastructure	VDL-M2 Digital Airborne Radio Transceiver	Aircraft must be fitted with a digital connection to a VHF Digital Radio (VDR) transceiver. • AEEC 631-B • DO-281B (RTCA Minimum Aviation System Performance) • ED-92B (EUROCAE MOPS)	ANSP	2013

Ground	Communicati	VDL-M2 Digital	VHF Digital Link Mode 2 system uses	ANSP	2013
system	on	Ground Radio	digital radios to improve the performance		
infrastructur	infrastructure	Transceiver	of VHF analog data link. VDL Mode 2		
е			provides a data rate of 31.5 kbit/second		
			using a radio channel that is the same		
			width as the channel used by the VHF		
			analog data link system, providing a data		
			rate of only 2.4 kbit/second. • DO-224C		
			(RTCA Minimum Aviation System		
			Performance Standard)		



Communicati on infrastructure	SATCOM Class C Usage and Data Protocol	SATCOM Performance Class C covers the performance requirements included in the current AMS(R)S SARPs and is applicable to systems already standardized in ICAO (such as Inmarsat Classic Aero, MTSAT and Iridium SBD) as well as the Inmarsat SBB system which was recently included in the AMS(R)S Manual. Class C is effectively covering remote and oceanic operations (Performance specification DO-306/ED-122). NGSS DO-210/DO-262	ANSP Satellite provider	2013
Communicati on infrastructure	SATCOM Class C Management Unit (Airborne Radio Transceiver)	AMSRS Satellite SARPS with Section for INMARSAT and Iridium AEEC 741, 761, 781-7 SATCOM Class C Form, Fit and Function	Aircraft manufacturer Satellite provider	2013
Communicati on infrastructure	SATCOM Class C Ground Radio Transceiver	Minimum Aviation System Performance Standards (MASPS) for the aeronautical mobile-satellite (R) service (AMS(R)S) as used in aeronautical data links.	ANSP	2013
Communicati on infrastructure	SATCOM Class C Space Radio Transceiver	Aeronautical Mobile Satellite (Route) Service Manual (Doc 9925) with a section that addresses Satcom Performance Class C	Satellite provider	2013
Communicati on infrastructure	Communication satellites for class C	Inmarsat I4, MTSAT and Iridium.	Satellite provider	2013
	Communicati on infrastructure  Communicati on infrastructure  Communicati on infrastructure  Communicati on infrastructure	on C Usage and Infrastructure Data Protocol  Communicati on C Management Unit (Airborne Radio Transceiver)  Communicati on C Ground Radio Infrastructure Transceiver  Communicati on C Space Radio Infrastructure Transceiver  Communicati on Satrom Class C Space Radio Infrastructure Transceiver  Communicati on Satellites for	the performance requirements included in the current AMS(R)S SARPs and is applicable to systems already standardized in ICAO (such as Inmarsat Classic Aero, MTSAT and Iridium SBD) as well as the Inmarsat SBB system which was recently included in the AMS(R)S Manual. Class C is effectively covering remote and oceanic operations (Performance specification DO-306/ED-122). NGSS DO-210/DO-262  Communicati of Management infrastructure Unit (Airborne Radio Transceiver)  Communicati of SATCOM Class on C Ground Radio infrastructure  Communicati of SATCOM Class on C Ground Radio infrastructure  Communicati of SATCOM Class on C Space Radio infrastructure  Communicati of C Space Radio infrastructure  C Space Radio	the performance requirements included in the current AMS(R)S SARPs and is applicable to systems already standardized in ICAO (such as Inmarsat Classic Aero, MTSAT and Iridium SBD) as well as the Inmarsat SBB system which was recently included in the AMS(R)S Manual. Class C is effectively covering remote and oceanic operations (Performance specification DO-306/ED-122). NGSS DO-210/DO-262  Communicati or C Management Unit (Airborne Radio Transceiver)  Communicati or C Ground Radio Infrastructure  SATCOM Class or C Ground Radio Infrastructure  Communicati or C Space Radio Infrastructure  Communicati or Satellite (Route)  Service Manual (Doc 9925) with a section that addresses Satcom Performance Class C  Communicati or Satellite Provider

COMI-B0/6	High Frequency Data Link (HFDL)  Technology
☐ Sixth edition of th	ne GANP 🚱
Main Purpose 2	To communicate in areas where SATCOM and VHF are not available.
New Capabilities ?	HFDL is a communications media used to exchange data messages between aircraft end-systems and corresponding ground-based HFDL ground stations.
	Supports improvement of surveillance in airspace where procedural separation is being applied.
Description ?	The HFDL includes the HFDL network and avionics. Specifically this means the introduction of an airborne communications router (e.g. Communications Management Unit) and an HFDL radio.
Maturity Level 2	Ready for implementation

### PLANNING LAYERS ②

Tactical-During ops

### **OPERATIONS ?**

En-route

### DEPENDENCIES AND RELATIONS @

There are currently no dependencies.

ENABLER	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Protocols	Communicati on infrastructure	HF Datalink operational Usage & Protocol	HFDL is an ACARS communications media that is used to exchange data between aircraft end-systems and ground based stations. • ARINC Specification 635-4: HF Data Link Protocols • ARINC Characteristic 753-2: HF Data Link System • ARINC Report 634: HF Data Link System Design Guidance Material • ICAO Doc. 9741 HFDL	ANSP Aircraft manufacturer	2013
Airborne system capability	Communicati on infrastructure	HFDL data radio transmission	To use High Frequency Data Links an aircraft needs to be equipped with a Communications Management Function or equivalent. This allow for airborne communications to interface with many aircraft communications systems. • DO-265 HFDL MOPS	ANSP Aircraft manufacturer	2013
Ground system infrastructur e	Communicati on infrastructure	HFDL ground radio transmission	• DO-277 MASPS	ANSP Aircraft manufacturer	2013

# COMI-B0/7 ATS Message Handling System (AMHS) Technology Sixth edition of the GANP Supports improved communication over AFTN Provide flight information coordination between ANSPs at adjacent FIRs, and with relevant military units, support separation assurance, potentially providing, when used in conjunction with other enablers (e.g. navigation capabilities), reduced separation.

- New Capabilities ? AMHS makes use of higher speed communication than AFTN. It also allows the use of bitoriented communications allowing greater flexibility in message types. Attachments to messages can also be supported thus allowing the exchange of graphics. Provides direct communication between adjacent FIRs using data communication to minimize the use of voice communication.
  - Increase performance to handle large files
  - Implement AFTN/AMHS gateway
  - Initiate the standardization of IP interface and addressing scheme

The AMHS is served as ICAO mandated communication for data exchange between ANSPs (ICAO Doc. 9880 and Annex X). AMHS is served as enabler for

- 1. Flight Plan/Clearance
- 2. AIDC: Flight transfer
- 3. MET data

ATS voice service is used for emergency coordination and/or normal coordination when data communication service is not available.

AMHS is expected to be utilized to carry traffic for AID C/Flight Plan/MET until SWIM is ready in Block 2. This is due to ANSPs need time to upgrade/implement adaptors to support SWIM interface. In the meantime, AMHS will accommodate SWIM compliance data message (IWXXM) as required. It is noted that AMHS would not be able to support FF-ICE and FIXM data.

The interface is based on IP over legacy dedicated point-to-point circuits.

Maturity Level ?

Ready for implementation

**Human Factor** Considerations

### PLANNING LAYERS ?

Tactical-During ops

### **OPERATIONS 2**

Departure En-route Arrival

### DEPENDENCIES AND RELATIONS @

Type of Dependencies **ASBU Element** 

COMI-B1/1 - Ground-Ground Aeronautical Telecommunication Relation-technology benefit

Network/Internet Protocol Suite (ATN/IPS)

### **ENABLERS**

Enabler **Enabler Type Enabler Name Description / References** Stakeholders Year Category

Duete cele	O = m = m : s = t!	AMUC	ATC Massacra Handling Cymhans (ANIHO)	ANIOD	2042
Protocols	Communicati on infrastructure	AMHS operational Usage & Protocol	ATS Message Handling Systems (AMHS) is a standard for aeronautical ground-to-ground communication. AMHS was first implemented by Avitech GmbH in 1996 and the first European AMHS connection was operational in 2005. The AMHS is a set of end systems that work together to allow cooperation between human and automated users. • ICAO Doc 4444, Procedures for Air Navigation Services Air Traffic Management • ICAO Doc 7030, Regional Supplementary Procedures • ICAO Doc 10037 Edition 1 • Global Operational Datalink Manual (GOLD) • ICAO Doc 9869 Second Edition • Performance-Based Communication and Surveillance (PBCS) Manual	ANSP	2013
Ground system infrastructur e	Communicati on infrastructure	Aviation Authority to Aircraft pilot data transmission	ICAO Doc 9880 Part II defines two fundamental levels of service within AMHS: basic and extended. The basic AMHS performs an operational role similar to the Aeronautical Fixed Telecommunication Network with some enhancements. • ED122/DO306, including Change 1 & 2, Oceanic Remote Safety and Performance Requirements • ED100A/DO258A, FANS 1/A Interoperability Requirements	ANSP	2013

### Ground-Ground Aeronautical Telecommunication Technology Network/Internet Protocol Suite (ATN/IPS) ☐ Sixth edition of the GANP ② Main Purpose ? To provide for a more modern, more efficient, cost-effective, and robust data communications network infrastructure. New Capabilities It enables the efficient integration of technologies with improved integrity to support future air to ground aeronautical safety services and regularity of flight communications. Description ? The ATN/IPS internetwork consists of IPS nodes and networks operating in a multinational environment in support of Air Traffic Service Communication (ATSC) as well as Aeronautical Industry Service Communication (AINSC), such as Aeronautical Administrative Communications (AAC) and Aeronautical Operational Communications. This evolution will support enhanced civil-military cooperation and coordination functions, if interoperability and military information security aspects are considered. Standardization Maturity Level ?

COMI-B1/1

### PLANNING LAYERS ?

Tactical-During ops

**OPERATIONS 2** 

En-route

### DEPENDENCIES AND RELATIONS @

Type of Dependencies **ASBU Element** 

Relation-technology benefit COMI-B1/4 - Aeronautical Mobile Airport Communication System

(AeroMACS) Ground-Ground

### **ENABLERS**

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Protocols	Communicati on infrastructure	IPS Protocol	The Manual on the Aeronautical Telecommunication Network (ATN) using Internet Protocol Suite (IPS) Standards and Protocols Doc 9896	ANSP	2019

### COMI-B1/2 VHF Data Link (VDL) Mode 2 Multi-Frequency Technology

☐ Sixth edition of the GANP ②

Main Purpose ?

- Supports transmission of data link message sets to supplement current voice operations, thus reducing voice channel congestion; while increasing productivity and capacity.
- Supports increased subnetwork capacity and reduces interference over the standard VDL Mode 2 system.

- New Capabilities Provides an increase in data capacity over VDL Mode 2
  - Exchanges aviation data (AOC, CPDLC and ADS)
  - Provides a supplement to voice communications
  - · More efficient use of spectrum

Description ?

VDL Mode 2 Multi-Frequency consists of a set of air-ground protocols that increase the data rate to 31.5 kbits. It allows transmission from a character oriented protocols to digital or bit based protocols while using VHF air and ground narrow-band transceiver operating in the VHF aviation protected spectrum band, which will transmit textual data to and from the cockpit to support data communications between the pilot and the air traffic controller.

Maturity Level ? Ready for implementation

**Human Factor** Considerations Tactical-During ops Taxi-out Departure En-route Arrival Taxi-in

### DEPENDENCIES AND RELATIONS @

Type of Dependencies ASBU Element

Evolution COMI-B0/4 - VHF Data Link (VDL) Mode 2 Basic

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Protocols	Communicati	VDL-M2 MF	• ICAO Doc 9776 VDL2 Technical Manual	ANSP	2019
	on infrastructure	operational Usage &	• ED-92B (EUROCAE MOPS) • DO-281B (RTCA Minimum Operational	Aircraft manufacturer	
		Protocol	Performance Standard) • AEEC 631-B • RTCA DO 224		
Airborne	Aircraft	Airborne VDL M-	VDL Mode 2 frequency management	ANSP	2019
system capability	· ·	2 MF autotune functionality	capability allow for auto-tune of an aircraft, from the VDL common signaling channel	Aircraft manufacturer	
			to an alternate VDL frequency, and back to the common signaling channel. The auto-tune command is the primary building block to instruct aircraft to tune to VDL frequencies, which enables service providers to actively manage traffic load among VDL frequencies. • DO-281B (RTCA Minimum Operational Performance Standard) • AEEC 631-6 • ED-92B (EUROCAE MOPS)		
Ground system infrastructur e	Communicati on infrastructure	Ground VDL M-2 MF autotune functionality	VDL Mode 2 frequency management capability allow for auto-tune of an aircraft, from the VDL common signaling channel to an alternate VDL frequency, and back to the common signaling channel. The auto-tune command is the primary building block to instruct aircraft to tune to VDL frequencies, which enables service providers to actively manage traffic load among VDL frequencies. • DO-224C (RTCA Minimum Aviation System Performance Standard) • DO-343A Minimum Aviation System Performance Standards (MASPS) for the Aeronautical Mobile-Satellite (R) Service (AMS(R)S) for FANS1/A+ • RTCA DO-262 MOPS	ANSP Aircraft manufacturer	2019

☐ Sixth edition of the GANP ②

Main Purpose ?

- Supports introduction of SATVOICE and SATDATA as a complement to HF voice communications.
- Provides for oceanic and domestic broadband IPS based safety critical data link operations.
- Supports safety critical, safety and regularity of flight operations.

- New Capabilities Use of SATCOM voice for all types of ATS communications (routine and emergency/urgency communications).
  - Provide high-speed IP based broadband networks.
  - Improved security
  - Lower cost than the traditional circuit switched services (Classic Aero).

Description ?

SATCOM System is a broadband, IP based communication system that provides voice and highspeed data communications between the aircraft and the air-traffic controller.

Two constellations are expected to provide this service (INMARSAT and Iridium).

SATCOM Class B (SB-S): SwiftBroadband is available over the Inmarsat 4 satellite constellation, providing near global coverage. SwiftBroadband includes SB-S avionics, the satellite modem that accesses the service, and the aircraft antenna capable of receiving SwiftBroadband and related equipment such as diplexer, LNA, HPA and cabling.

SATCOM Class B (Certus)The Iridium NEXT (Certus) Satellite Network, with its constellation of 66 Low Earth Orbit (LEO) satellites, is a global mobile satellite communication network, with coverage of the entire Earth, including polar regions, offering ATC voice and data service.

This evolution will support enhanced civil-military cooperation and coordination functions, if interoperability and military information security aspects are considered.

Maturity Level ?

Ready for implementation

Human Factor Considerations

### PLANNING LAYERS ?

Tactical-During ops



Departure En-route Arrival

### DEPENDENCIES AND RELATIONS @

There are currently no dependencies.

### **ENABLERS**

Enabler **Enabler Type** Enabler Name **Description / References** Stakeholders Year Category

**Protocols** 

on

Communicati SATCOM Class B usage and infrastructure protocols

SB-S is the INMARSAT Satellite System

(2019). SATCOM Performance Class B covers more stringent (compared to Class C) performance requirements and will be

applicable to commercial SATCOM systems, (i.e. the Iridium Next and the Inmarsat SB-S supporting safety services.

SATCOM Performance Class B covers the performance requirements of initial 4D

operations and the Baseline 2 (B2) requirements defined by RTCA and

EUROCAE. Performance Class B

requirements will cover remote, oceanic as well as continental/domestic

operations. Global Operational Data Link

Document (GOLD) Manual (Doc 10037),

the PBCS Manual (DOC 9869) and the Satellite Voice Guidance Material (SVOM,

Doc 10038) Performance specification

DO-306/ED-122; DO-290/ED-120

Interoperability Specification DO-

258A/ED-100A DO-280B/ED-112B

Certus is the Iridium Next Satellite System (2025). SATCOM Performance Class B

covers more stringent (compared to Class

C) performance requirements and will be applicable to commercial SATCOM

systems, (i.e. the Iridium Next and the

Inmarsat SB-S supporting safety services.

SATCOM Performance Class B covers the performance requirements of initial 4D

operations and the Baseline 2 (B2)

requirements defined by RTCA and

EUROCAE. Performance Class B

requirements will cover remote, oceanic

as well as continental/domestic

operations. Performance specification

DO-306/ED-122 DO-350A/ED-228A

Interoperability Specification DO-

258A/ED-100A DO-351A/ED-229A

RTCA DO 262 MOPS Certus Technical Manual The AMS(R)S manual (Doc 9255),

separate chapter for the IridiumNext

(Certus) system Global Operational Data

Link Document (GOLD) Manual (Doc

10037), the PBCS Manual (DOC 9869)

and the Satellite Voice Guidance Material

(SVOM, Doc 10038)

**ANSP** 

2019

Aircraft manufacturer

				Aircraft	
Airborne system capability	Communicati on infrastructure	SATCOM Class B Management Unit (Airborne Radio Transceiver)	AEEC Characteristic, 771 / 781 (INMARSAT; 2019) RTCA DO 262 MOPS Certus Technical Manual (Iridium;2025) AEEC 771-2 SATCOM Class B Form, Fit and Function (Iridium;2025)	manufacturer	2019
Ground			RTCA DO-343 MASPS	ANSP	2019
system infrastructur	on infrastructure	B Ground Radio Transceiver	(INMARSAT;2019) DO-343B Minimum Aviation System Performance Standards	Aircraft manufacturer	urer
е			(MASPS) for the Aeronautical Mobile- Satellite (R) Service (AMS(R)S) For FANS1/A+ and ATN/IPS (Iridium;2025)		
Space Communicati	Communication	Swift Broadband Safety Satellite (2019):	Satellite provider	2019	
system infrastructur e	on infrastructure	satellites for class B	The AMS(R)S manual (Doc 9925), separate chapter for the Inmarsat SB- Safety systems Certus Satellite (2025): Performance specification DO-306/ED-		
			122 DO-350A/ED-228A Interoperability Specification DO-258A/ED-100A DO- 351A/ED-229A		

COMFB1/4	Aeronautical Mobile Airport Communication Technology System (AeroMACS) Ground-Ground
☐ Sixth edition of the	e GANP ②
Main Purpose 2	<ul> <li>Reduced Separation</li> <li>Improved situational awareness</li> <li>Reduced Cost</li> <li>Improved Efficiency</li> </ul>
New Capabilities 2	<ul> <li>Broadband Communications</li> <li>Supports Safety communications</li> <li>IPS Based System</li> <li>Improved Security</li> </ul>
Description ?	AeroMACS is a broadband wireless communications system. It can provide network connectivity on the airport surface for fixed wireless communications and can be used only for the safety critical and regularity of flight. The fixed assests supported by AeroMACS include multilateration sensors, weather sensors, surface radar and fixed navigation aids.
Maturity Level    Output  Description:	Ready for implementation
Human Factor Considerations	

OPERATIONS 2

PLANNING LAYERS 2

Taxi-out Taxi-in

### DEPENDENCIES AND RELATIONS 2

There are currently no dependencies.

ENABLER	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Operational procedures	-	AeroMACS operational description	• ED222 / Do345: Aeronautical Mobile Airport Communications System (AeroMACS) Profile Doc. • Doc 10044: AeroMACS Technical Manual	ANSP	2017
Ground system infrastructur e	Airport systems	AeroMACS Mobile Station (Ground Radio Unit)	•ED223 / Do346: Minimum Operational Performance Standards (MOPS) for the AeroMACS. •ICAO ANNEX-10, Volume III, Chapter 7: AeroMACS SARPs	Airport operator	2017
Ground system infrastructur e	Communicati on infrastructure	AeroMACS Base Station	EUROCAE ED-227: AeroMACS MASPS	ANSP	2017

COMI-B2/1	Air-Ground ATN/IPS	Technology
☐ Sixth edition of the	e GANP <b>②</b>	
Main Purpose  To improve integrity of the information.		
New Capabilities 2	This element:	
	<ul><li>provides more efficient data commu</li><li>improves information integrity.</li></ul>	nications;
Description		Internet Protocol (IP) that promises to use Commercial-Offair to ground aeronautical safety services and regularity of
Maturity Level	Validation	
Human Factor Considerations		
PLANNING L	AYERS •	OPERATIONS 2
Tactical-During o	ps	En-route

DEPENDENCIES AND RELA	TIONS O
Type of Dependencies	ASBU Element
Relation-technology option	COMI-B1/2 - VHF Data Link (VDL) Mode 2 Multi-Frequency
Relation-technology option	COMI-B1/3 - SATCOM Class B Voice and Data
Relation-technology benefit	COMI-B3/1 - VHF Data Link (VDL) Mode-2 Connectionless
Relation-technology benefit	COMI-B3/2 - SATCOM Class A voice and data
Relation-technology benefit	COMI-B3/4 - Links meeting requirements for safety critical communication
Relation-technology benefit	COMI-B3/3 - L-band Digital Aeronautical Communication System (LDACS)
Relation-technology benefit	COMI-B2/2 - Aeronautical Mobile Airport Communication System (AeroMACS) aircraft mobile connection

Protocols Communicati IPS Protocol The Manual on the Aeronautical Telecommunication Network (ATN) using Internet Protocol Suite (IPS) Standards and Protocols Doc 9896  Airborne Communicati IPS Airborne system on Router (IPS) ICAO ANNEX-10, Volume III, IPS Aircraft operator  Aircraft manufacturer 2025  Aircraft manufacturer SARPs ARINC Project Paper 858 IPS technical requirements	ENABLERS	5				
on infrastructure Internet Protocol Suite (IPS) Standards and Protocols Doc 9896  Airborne Communicati IPS Airborne system on Router (IPS) ICAO ANNEX-10, Volume III, IPS SARPs ARINC Project Paper 858 IPS technical requirements  Ground Communicati IPS Ground IPS MASPS  Telecommunication Network (ATN) using Internet Protocol Suite (IPS) Standards and Protocols Doc 9896  Aircraft manufacturer 2025  Aircraft operator 2025  Aircraft operator 2025		Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Airborne Communicati IPS Airborne Aviation Profiles for Internet Protocol Suite manufacturer  system on Router (IPS) ICAO ANNEX-10, Volume III, IPS capability infrastructure SARPs ARINC Project Paper 858 IPS technical requirements  Ground Communicati IPS Ground IPS MASPS  ANSP 2025		on	IPS Protocol	Telecommunication Network (ATN) using Internet Protocol Suite (IPS) Standards	ANSP	2019
	system	on		(IPS) ICAO ANNEX-10, Volume III, IPS SARPs ARINC Project Paper 858 IPS	manufacturer Aircraft	2025
infrastructure infrastructure	system	on		IPS MASPS	ANSP	2025

COMI-B2/2	Aeronautical Mobile Airport Communication Technology  System (AeroMACS) aircraft mobile connection
☐ Sixth edition of the	e GANP ②
Main Purpose 2	To reduce separation and improve situational awareness.
New Capabilities 2	<ul> <li>Broadband communications.</li> <li>Supports safety communications.</li> <li>IPS based system.</li> <li>Improved security.</li> </ul>

Description ?

AeroMACS is a broadband wireless communications system. It can provide network connectivity on the airport surface for communications to mobile assets (e.g. Aircraft, emergency vehicles, baggage trucks). It is used to transmit safety critical and regularity of flight information.

Maturity Level 2

Validation

Human Factor
Considerations

### PLANNING LAYERS 2

Tactical-During ops



Taxi-out Taxi-in

### DEPENDENCIES AND RELATIONS 2

There are currently no dependencies.

ENABLER	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Operational procedures	-	AeroMACS mobile connection operational description	• ED222 / Do345: Aeronautical Mobile Airport Communications System (AeroMACS) Profile Doc. • Doc 10044: AeroMACS Technical Manual	ANSP	2031
Airborne	Communicati	AeroMACS	• ED223 / Do346: Minimum Operational	Aircraft manufacturer	2031
system capability	on infrastructure	Mobile Station (Avionics Radio Unit)	Performance Standards (MOPS) for the AeroMACS. • ICAO ANNEX-10, Volume III, Chapter 7: AeroMACS SARPs • ARINC 766: Aeronautical Mobile Airport Communication System (AeroMACS) Transceiver and Aircraft Installation Standards	Aircraft operator	
Ground system infrastructur e	Communicati on infrastructure	AeroMACS Base Station for mobile connection	EUROCAE ED-227: AeroMACS MASPS	ANSP	2031

# COMI-B2/3 Links meeting requirements for non-safety critical Technology communication

☐ Sixth edition of the GANP ②

Main Purpose ?

- reduce operational cost;
- improve performance;
- take advantage of new technologies sooner;
- enable the global exchange of non-safety information.

- New Capabilities Improved resiliency
  - · Reduced operational costs
  - Improved capacity
  - Broadband communications
  - Enable a single IP-based global operating network

Description ?

Broadband satellite and cellular services are used to support non-safety critical communications. By adopting the use of available infrastructure and possibly the use of a multi-sensor concept these systems meet performance requirements, in effect leading to reduced system cost, while improving the overall performance of the network and the system resiliency.

Maturity Level ?

Validation

**Human Factor** Considerations

### PLANNING LAYERS ?

Tactical-During ops



### DEPENDENCIES AND RELATIONS @

There are currently no dependencies.

ENABLER					
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Airborne	Communicati	Commercial	In the future commercial provider (Ex.	ANSP	2025
system capability	on infrastructure	airborne data transfer	AWS, Azure, Google) may increase their range and service offerings to allow implementation of radio systems that can be used to transfer data from airborne systems to ground systems.	Communication service provider	
Ground	Communicati	Commercial	To reduce congestion on current air traffic	ANSP	2025
system infrastructur	on infrastructure	ground data transfer	control towers, commercial cellular infrastructure and systems already in	Communication service provider	
е			place can be used to relay data.		

Space Communicati Commercial system on satellite data infrastructur infrastructure transfer

To relay messages via satellites while saving the cost on implementation, commercial broadband satellites and constellation systems (Ex. Amazon, Google, SpaceX) can be used to relay data.

ANSP Satellite provider 2025

COMI-B3/1 VHF Data Link (VDL) Mode-2 Connectionless Technology

☐ Sixth edition of the GANP ②

Main Purpose **?** To make a more efficient use of the bandwith.

New Capabilities **?** Connection-less mode 2 uses a previously dormant feature (unnumbered information frames) instead of information frames.

Description Oconnection-less VDL 2 is capable of transporting AOA messages, ATN messages and IPS messages. It reduces connection orientated complexity; while being efficient in its use, and extending the lifetime of the finite number of VDL 2 channels available. It is determined to be less complicated overall and a larger percentage of the complexity is in the ground system where it's

easier to maintain and less expensive.

Additionally, connection-less will provide better performance (fewer Provider Aborts and lower propagation times).

This evolution offers opportunities for compliance based on performance-equivalence for State aircraft.

Maturity Level ? Concept

Human Factor
Considerations

PLANNING LAYERS ②

Tactical-During ops

**OPERATIONS 2** 

Taxi-out Departure En-route

ute Arrival

Taxi-in

DEPENDENCIES AND RELATIONS 2

Type of Dependencies ASBU Element

Evolution COMI-B0/4 - VHF Data Link (VDL) Mode 2 Basic

**ENABLERS** 

Enabler Type Enabler Name Description / References Stakeholders Year

Category

Protocols	Communicati on infrastructure	Connectionless VDL-M2 operational usage & protocols	• ICAO Doc 9776 VDL2 Technical Manual • AEEC 631-6 • DO-281B (RTCA Minimum Operational Performance Standard) • ED-92B (EUROCAE MOPS) • DO-224C (RTCA Minimum Aviation System Performance Standard)	ANSP Aircraft manufacturer	2030
Airborne system capability	Communicati on infrastructure	Connectionless VDL-M2 Digital Airborne Radio Transceiver	Existing VDL Mode 2 requires airplanes and ground stations to establish an explicit connection. This is less efficient than connectionless VDL Mode 2 because of resulting overhead message traffic for link establishment, ground station handoff, etc. Existing VDL Mode 2 is also less robust because airplanes will accept an uplink only from a connected ground station and ground stations will accept a downlink only from a connected airplane. • AEEC 631-6 • DO-281B (RTCA Minimum Operational Performance Standard) • ED-92B (EUROCAE MOPS)	ANSP  Aircraft manufacturer	2025
Ground system infrastructur e	Communicati on infrastructure	Connectionless VDL-M2 Digital Ground Radio Transceiver	Existing VDL Mode 2 requires airplanes and ground stations to establish an explicit connection. This is less efficient than connectionless VDL Mode 2 because of resulting overhead message traffic for link establishment, ground station handoff, etc. Existing VDL Mode 2 is also less robust because airplanes will accept an uplink only from a connected ground station and ground stations will accept a downlink only from a connected airplane. • DO-224C (RTCA Minimum Aviation System Performance Standard)	ANSP  Aircraft manufacturer	2025

COMFB3/2	SATCOM Class A voice and data	Technology
Sixth edition of the	e GANP 🕖	
Main Purpose	To improve efficiency and cost-effectiveness of defines more stringent (compared to Class B) p future concepts of SESAR/NextGen/CARATS.	
New Capabilities 2	<ul><li>Improved resiliency</li><li>Reduced operational costs</li><li>Improved capacity</li><li>Support B3 Message Sets</li></ul>	

Description 2

SATCOM Class A will make use of existing and future commercially available constellations to provide multilink operations and thus improved capacity, availability and resiliency.

This evolution offers opportunities for compliance based on performance-equivalence for State aircraft.

Maturity Level ?

Concept

**Human Factor** Considerations

### PLANNING LAYERS 3

Tactical-During ops

### **OPERATIONS 3**

Taxi-out Departure Arrival

### DEPENDENCIES AND RELATIONS @

There are currently no dependencies.

### **ENABLERS**

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Protocols	Communicati on infrastructure	SATCOM Class A operational usage and protocols	SATCOM Performance Class A covers more stringent (compared to Class B) performance requirements and will be applicable to future SATCOM systems SATCOM Performance Class A covers the performance requirements of full 4D operations and operations required to support the SESAR/NextGEN/CARATS future concepts. SATCOM Performance Class A requirements correspond to the Baseline 3 (B3) requirements. Class A will cover remote, oceanic as well as continental operations/domestic. Class A performance requirements are expected to serve in particular as design guidelines for the definition and specification of future SATCOM systems to support the future aviation requirements.	ANSP	2031

COMI-B3/3

L-band Digital Aeronautical Communication System (LDACS)

Technology

☐ Sixth edition of the GANP ②

Main Purpose ? To:

- support improved Message Sets (B2) including accurate aircraft trajectory for improved 4D flight
- provide for more efficient data communications;
- · increase security.

- New Capabilities 
   Broadband communications.
  - Supports safety communications.
  - IPS based system.
  - Improved security.

Description ?

LDACS (L-band Digital Aeronautical Communications System) is the future terrestrial air-ground data link. It is a frequency division duplex (FDD) configuration utilizing Orthogonal Frequency Division Multiplexing (OFDM), reservation based access control and advance network protocols (i.e. IPS).

Maturity Level ?

Validation

**Human Factor** Considerations

### PLANNING LAYERS ?

Tactical-During ops



Taxi-out Departure En-route Arrival Taxi-in

### DEPENDENCIES AND RELATIONS @

There are currently no dependencies.

### **ENABLERS**

There are currently no enablers.

### COMI-B3/4

Links meeting requirements for safety critical communication

Technology

☐ Sixth edition of the GANP ②

Main Purpose 2 To:

- provide more efficient data communications;
- increase security;
- · reduce cost;
- improve performance;
- · take advantage of newer technologies sooner;
- enable the global exchange of safety critical information.

- New Capabilities 
   Broadband Communications
  - Supports Safety communications
  - IPS Based System
  - Improved Security
  - Enable a single IP-based global operating network for all information

Description ?

Broadband satellite and cellular services are used for safety-critical communications. Through the use of a multi-sensor concept, a combination of these systems can be used together to meet the safety critical and regularity of flight performance, interoperability and certification requirements, reducing the system cost while improving the overall performance of the network and the resiliency of the system. LDACS and AeroMACS are other candidate solutions for use in the en-route/terminal area and airport surface respectively.

Maturity Level ?

Concept

**Human Factor** Considerations

### PLANNING LAYERS ②

Tactical-During ops



Taxi-out Departure En-route Arrival

Taxi-in

### **DEPENDENCIES AND RELATIONS @**

There are currently no dependencies.

ENABLER	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Ground system infrastructur e	Communicati on infrastructure	Commercial ground system use	Future improvements to ground based commercial systems will allow safety critical information to be transferred on existing commercial systems.	Communication service provider	2031
Space system infrastructur e	Communicati on infrastructure	Commercial space system use	Future improvements to satellite-based data transfer services as well as the addition of new satellites will allow safety critical communication to utilize commercial satellites. Likely require exploration of hybrid satellite constellation services	Communication service provider	2031

☐ Sixth edition of the GANP ②

### Main Purpose 2 Supports:

- · reduction of voice channel congestion and increase of capacity in domestic airspace,
- improvement of communication and surveillance in airspace where procedural separation is being applied.
- New Capabilities As a complement to voice communications, controller–pilot data link communications (CPDLC) provides the controller and the pilot with the ability to communicate through exchange of data link messages.
- Description **O** Depending on the specific implementations, other advantages associated with CPDLC include:
  - 1. in certain airspace, direct controller-pilot communications (DCPC) where it was not previously available;
  - 2. allowing the flight crew to print messages;
  - 3. allowing messages to be stored and reviewed as needed;
  - reducing flight crew-input errors by allowing the loading of information from specific uplink
    messages, such as route clearances or frequency change instructions, into other aircraft systems,
    such as the FMS or radios;
  - 5. allowing the flight crew to request complex route clearances, which the controller can respond to without having to manually enter a long string of coordinates;
  - reducing flight crew workload by supporting automatically transmitted reports when a specific event occurs, such as crossing a waypoint and the loading of clearance information directly into the flight management system; and
  - 7. reducing controller workload by providing automatic flight plan updates when specific downlink messages (and responses to some uplink messages) are received.

For domestic airspaces, **ATN B1 CPDLC services** provide management of the ATC data link and voice communications, check of ATC microphone stuck and exchange of a limited set of ATC clearances and requests. The vast majority of ATN B1 aircraft do not support any automatic integration of CPDLC instructions into the aircraft Flight Management System.

For procedural airspaces, **FANS 1/A CPDLC services** provide management of the ATC data link and voice communications, exchange of an extensive set of ATC clearance and requests, reporting of aircraft derived information (including Position Reporting). The vast majority of FANS 1/A aircraft support automatic integration of CPDLC instructions into the aircraft Flight Management System (even though implementations are not harmonized across the fleet due to lack of standardization).

Maturity Level ? Ready for implementation

Human Factor Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes

DEPENDENCIES AND REL	ATIONS 2
Type of Dependencies	ASBU Element
Relation-technology option	COMI-B0/1 - Aircraft Communication Addressing and Reporting System (ACARS)
Relation-technology option	COMI-B0/2 - Aeronautical Telecommunication Network/Open System Interconnection (ATN/OSI)

Enabler	<b>Enabler Type</b>	<b>Enabler Name</b>	Description / References	Stakeholders	Year
Category					
Operational	Communicati	CPDLC	Requirements and guidance to support	ANSP	2013
procedures	on service	,	Aircraft manufacturer		
			Procedures for Air Navigation Services Air Traffic Management ICAO Doc 10037  Aircraft operator		
			Edition 1 Global Operational Datalink Manual (GOLD)		
Airborne	Communicati	FANS 1/A	Technical standards to ensure operational	Aircraft manufacturer	2002
system capability	on service	CPDLC aircraft system	and technical interoperability, such as : Annex 10 Vol II ED100/DO258, FANS 1/A	Aircraft operator	
			Interoperability Requirements		
Airborne	Communicati		Technical standards to ensure operational and technical interoperability, such as : Annex 10 Vol II ED110B/DO280B, ATN	Aircraft manufacturer	2007
system on servi capability	on service			Aircraft operator	
			B1 Interoperability Requirements ED120/DO290, Domestic SPR	орогало.	
Ground	Communicati	FANS 1/A	Technical standards to ensure operational	ANSP	200
system nfrastructur	on service	CPDLC Ground System	and technical interoperability, such as : Annex 10 Vol II ED100/DO258, FANS 1/A Interoperability Requirements	Ground systems supplier	
Ground	Communicati	ATN B1 CPDLC	Technical standards to ensure operational	ANSP	200
system nfrastructur	on service	Ground System	and technical interoperability, such as : Annex 10 Vol II ED110B & ED120	Ground systems supplier	
e			ED100/DO258, FANS 1/A Interoperability Requirements		
Training	Communicati	Training	Flight Crew Training, Maintenance and	ANSP	201
	on service	requirements for CPDLC (FANS	Flight Operations Training, controllers training ICAO Doc 10037 Edition 1	Aircraft manufacturer	
		1/A & ATN B1) for domestic and	Global Operational Data link Manual (GOLD)	Aircraft operator	

Regulatory provisions	Equipage requirements or/and mandates	CPDLC Requirements and/or mandates	Airspace requirements and separation standards, with associated means of compliance. References: Amendment of Regional Supplementary Procedures – Doc 7030 (PAC, NAT and EUR)	ANSP Aircraft operato	2013
Regulatory provisions	SMS	CPDLC Safety Management System	Requirements to support local safety cases. References: Annex 19 Annex 11 PANS ATM 4444	ANSP	2013

COMS-B0/2	ADS-C (FANS 1//	A) for procedural airspace Technology		
Sixth edition of the	ne GANP ②			
Main Purpose ?	Supports improve	ment of surveillance in airspace where procedural separation is being applied.		
New Capabilities ?	ADS-C (FANS 1/A	A) provides aircraft position and projected route information (i.e. next two of aircraft).		
Description 2	concerning the air	bility provides automatically, without pilot intervention, an ATS unit with information craft position and projected profile for the flight at time intervals, events or on by the ground needs.		
Maturity Level 2	Ready for implement	entation		
Human Factor Considerations	1. Does it imply a change in task by a user or affected others? Yes			
	2. Does it imply processing of new information by the user? Yes			
	3. Does it imply the use of new equipment? Yes			
	4. Does it imply a	change to levels of automation? Yes		
PLANNING L	AYERS 👩	OPERATIONS 2		
Tactical-During o	pps	En-route		
DEPENDENC	CIES AND RELAT	TIONS @		
Type of Depende	encies	ASBU Element		
Relation-technolo	ogy need	COMI-B0/1 - Aircraft Communication Addressing and Reporting System (ACARS)		
ENABLERS				

**Description / References** 

Stakeholders

Year

Enabler

Category

**Enabler Type** Enabler Name

Operational procedures	Communicati on service	ADS-C procedures and monitoring	Requirements and guidance to support deployment of CPDLC operations, such as: Annex 10 Vol II ICAO Doc 4444, Procedures for Air Navigation Services Air Traffic Management ICAO Doc 10037 Edition 1 Global Operational Datalink Manual (GOLD)	ANSP Aircraft manufacturer Aircraft operator	2013
Airborne system capability	Communicati on service	FANS 1/A ADS- C aircraft system	Technical standards to ensure operational and technical interoperability, such as : Annex 10 Vol II ED100/D0258, FANS 1/A Interoperability Requirements	Aircraft manufacturer Aircraft operator	2002
Ground system infrastructur e	Communicati on service	FANS 1/A ADS- C Ground System	Technical standards to ensure operational and technical interoperability, such as : Annex 10 Vol II ED100/D0258, FANS 1/A Interoperability Requirements	ANSP Ground systems supplier	2002
Training	Communicati on service	Training requirements for ADS-C (FANS 1/A) for procedural airspace	Flight Crew Training, Maintenance and Flight Operations Training and air traffic controllers ICAO Doc 10037 Edition 1 Global Operational Datalink Manual (GOLD)	ANSP Aircraft manufacturer Aircraft operator	2013
Regulatory provisions	Equipage requirements or/and mandates	ADS-C Requirements and/or mandates	Airspace requirements and separation standards, with associated means of compliance. References: Amendment of Regional Supplementary Procedures – Doc 7030 (PAC and NAT)	ANSP CAA Aircraft operator	2013
Regulatory provisions	SMS	ADS-C Safety Management System	Requirements to support local safety cases. References: Annex 19 Annex 11 PANS ATM 4444	ANSP	2013

COMS-B1/1	PBCS approved CPDLC (FANS 1/A+) for domestic and procedural airspace	echnology
☐ Sixth edition of th	e GANP 🕖	
Main Purpose 2	Supports:	
	<ul> <li>reduction of voice channel congestion and increas</li> <li>introduction of performance-based reduced separ</li> </ul>	
New Capabilities ?	FANS 1/A+ CPDLC systems (along with associated demonstrated compliant with RCP240 (procedural) a	

Description ?

In procedural airspace, RCP240 authorized CPDLC (FANS 1/A+) provides the controller with intervention capability, allowing when used in conjunction with other enablers (e.g. ADS-C and navigation capabilities), reduced separation minima and thus capacity increase.

In domestic airspace, RCP 130 compliant CPDLC (FANS 1/A+) provides a complementary means of communications for en-route routine communications and the extension of CPDLC for ground operations (e.g. departure clearance).

PBCS will also enhance airspace access for State aircraft as it would offer opportunities for application of performance-equivalence.

Maturity Level ?

Ready for implementation

**Human Factor** Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes



Tactical-Pre ops Tactical-During ops



Departure En-route

### DEPENDENCIES AND RELATIONS @

**ASBU Element** Type of Dependencies

COMS-B0/1 - CPDLC (FANS 1/A & ATN B1) for domestic and procedural **Evolution** 

airspace

### ENIARIERO

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Operational Communicati procedures on service	CPDLC procedures and monitoring	Requirements and guidance to support deployment of CPDLC operations, such as: Annex 10 Vol II ICAO Doc 4444,  ANSP  Aircraft manufacturer	2013		
		, and	Procedures for Air Navigation Services Air Traffic Management ICAO Doc 10037 Edition 1 Global Operational Datalink Manual (GOLD)	Aircraft operator	
	Communicati on service		Guidance to support deployment of Performance Based operations, such as: ICAO Doc 9869 Third Edition Performance-Based Communication and Surveillance (PBCS) Manual	ANSP Aircraft manufacturer	-
				Aircraft operator  Communication service provider	

Airborne system capability	Communicati on service	FANS 1/A+ CPDLC aircraft system	Technical standards to ensure operational and technical interoperability, such as: Annex 10 Vol II ED122/DO306, including Change 1 & 2, Oceanic Remote Safety and Performance Requirements ED100A/DO258A, FANS 1/A+ Interoperability Requirements	Aircraft manufacturer Aircraft operator	2007
Ground system infrastructur e	Communicati on service	FANS 1/A+ CPDLC Ground System	Technical standards to ensure operational and technical interoperability, such as: Annex 10 Vol II ED122/DO306, including Change 1 & 2, Oceanic Remote Safety and Performance Requirements ED100A/DO258A, FANS 1/A+ Interoperability Requirements	ANSP Ground systems supplier	2007
Training	Communicati on service	Training requirements for PBCS approved CPDLC (FANS 1/A+) for domestic and procedural airspace	Controllers training, Flight Crew Training, Maintenance and Flight Operations Training. ICAO Doc 10037 Edition 2 Global Operational Datalink Manual (GOLD)	ANSP Aircraft manufacturer Aircraft operator	2019
Regulatory	Equipage requirements or/and mandates	CPDLC PBCS Requirements and/or mandates	Airspace requirements and separation standards, with associated means of compliance. References: Amendment of Regional Supplementary Procedures – Doc 7030 (PAC and NAT) Annex 6 Annex 11 Annex 15 ICAO Doc 9869 Second Edition Performance-Based Communication and Surveillance (PBCS) Manual	ANSP CAA  Aircraft operator	2016
Regulatory provisions	SMS	CPDLC PBCS Safety Management System	Requirements to support local safety cases. References: Annex 19 Annex 11 PANS ATM 4444	ANSP	2013
Regulatory provisions	Operational Approval	PBCS Approval	Requirements and guidance for PBCS operational authorization in Annex 6 and Doc 9869, 3rd Edition	CAA Aircraft operator	2019

COMS-B1/2	PBCS approved ADS-C (FANS 1/A+) for procedural airspace	Technology
☐ Sixth edition of t	he GANP 2	
Main Purpose 2	Supports introduction of performance-based red	duced separation minima in procedural airspace.

New Capabilities FANS 1/A+ ADS-C systems (along with associated air-ground network and physical layers) are demonstrated compliant with RSP180.

Description ?

ADS-C (FANS 1/A) RSP180 authorized provides separation assurance, allowing when used in conjunction with other enablers (e.g. CPDLC and navigation capabilities), reduced separation minima and thus capacity increase.

PBCS will also enhance airspace access for State aircraft as it would offer opportunities for application of performance-equivalence.

Ready for implementation Maturity Level ?

Human Factor Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes

### PLANNING LAYERS 3

Tactical-During ops

**OPERATIONS ?** 

En-route

### **DEPENDENCIES AND RELATIONS 3**

Type of Dependencies **ASBU Element** 

**Evolution** COMS-B0/2 - ADS-C (FANS 1/A) for procedural airspace

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Operational procedures	Communicati on service	ADS-C procedures and monitoring	Requirements and guidance to support deployment of CPDLC operations, such as: Annex 10 Vol II ICAO Doc 4444, Procedures for Air Navigation Services Air Traffic Management ICAO Doc 10037 Edition 1 Global Operational Datalink Manual (GOLD)	ANSP Aircraft manufacturer Aircraft operator	2013
Airborne system capability	Communicati on service	FANS 1/A+ ADS-C aircraft system	Technical standards to ensure operational and technical interoperability, such as: Annex 10 Vol II ED122/DO306, including Change 1 & 2, Oceanic Remote Safety and Performance Requirements ED100A/DO258A, FANS 1/A+ Interoperability Requirements	Aircraft manufacturer  Aircraft operator	2007

Ground system infrastructur e	Communicati on service	FANS 1/A+ ADS-C Ground System	Technical standards to ensure operational and technical interoperability, such as: Annex 10 Vol II ED122/DO306, including Change 1 & 2, Oceanic Remote Safety and Performance Requirements ED100A/DO258A, FANS 1/A+ Interoperability Requirements	ANSP Ground systems supplier	2007
Training	Communicati on service	Training requirements for PBCS approved ADS-C (FANS 1/A+) for procedural airspace	Controllers training, Flight Crew Training, Maintenance and Flight Operations Training. ICAO Doc 10037 Edition 1 Global Operational Datalink Manual (GOLD)	ANSP Aircraft manufacturer Aircraft operator	2016
Regulatory provisions	SMS	ADS-C Safety Management System	Requirements to support local safety cases. References: Annex 19 Annex 11 PANS ATM 4444	ANSP	2013
Regulatory provisions	Equipage requirements or/and mandates	ADS-C PBCS Requirements and/or mandates	Airspace requirements and separation standards, with associated means of compliance. References: Amendment of Regional Supplementary Procedures – Doc 7030 (PAC and NAT) Annex 6 Annex 11 Annex 15 ICAO Doc 9869 Second Edition Performance-Based Communication and Surveillance (PBCS) Manual	ANSP CAA Aircraft operator	2016
Operational procedures		Datalink performance requirements and monitoring (ADS- C)	Guidance to support deployment of Performance Based operations, such as: ICAO Doc 9869 Second Edition Performance-Based Communication and Surveillance (PBCS) Manual	ANSP Aircraft manufacturer Aircraft operator Communication service provide	
Regulatory	Operational Approval	PBCS Approval (RSP 180)	Requirements and guidance for PBCS operational authorization in Annex 6 and Doc 9869, 2nd Edition	CAA Aircraft operator	2016

COMS-B1/3	SATVOICE (incl. routine communications) for Technology procedural airspace
☐ Sixth edition of the	e GANP ②
Main Purpose ?	Increase quality of voice communications in procedural airspace without VHF coverage.
New Capabilities 2	Use of SATVOICE for all types of ATS communications (routine and emergency/urgency communications).

Description ?

A priority level is used by dedicated networks and the aircraft system to pre-empt calls of lower priority, if necessary, and establish precedence for incoming calls of higher priority (usually routine ATS communication will be Priority 2 out of 4, Priority 1 being dedicated to distress/urgent calls).

PBCS will also enhance airspace access for State aircraft as it would offer opportunities for application of performance-equivalence.

Maturity Level ?

Ready for implementation

Human Factor Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes



Tactical-During ops

**OPERATIONS 2** 

En-route

### DEPENDENCIES AND RELATIONS 2

Type of Dependencies ASBU Element

Relation-technology need COMI-B0/5 - Satellite communications (SATCOM) Class C Data

ΔR	

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Regulatory provisions	Equipage requirements or/and mandates	Requirements for the use of SATVOICE	Annex 10 , Volume III Annex 4 PANS-ATM (Doc 4444) PANS-AIM (Doc 10066)	ANSP CAA  Aircraft manufacturer  Aircraft operator  Communication service provider	2016
Regulatory provisions	SMS	SATVOICE Safety Management System	Requirements to support local safety cases. References: Annex 19 Annex 11 PANS ATM 4444	Satellite provider ANSP	2013
Operational procedures	-	SATVOICE procedures	Doc 10038, Satellite Voice Operations Manual (SVOM)	ANSP Aircraft manufacturer Aircraft operator	2019

Operational	-	SATVOICE	Reference: Performance-Based	ANSP	2016
procedures	performance monitoring	Communication and Surveillance (PBCS)  Manual, Second Edition.	Aircraft manufacturer		
			Aircraft operator		
				Communication service provider	
Airborne	Aircraft	SATVOICE	References: Annex 10, Volume III Manual	Aircraft manufacturer	2016
system capability	system	airborne system	on the Aeronautical Mobile Satellite (Route) Service. (Doc 9925)	Aircraft operator	
Ground	-	SATVOICE	References: Annex 10, Volume III Manual	ANSP	2016
system infrastructur e		ground system	on the Aeronautical Mobile Satellite (Route) Service. (Doc 9925)	Ground systems supplier	
Training	-	Training requirements for	SATVOICE training for flight crew, radio operator and air traffic controller	ANSP	2019
		SATVOICE	References: Doc 10038, Satellite Voice Operations Manual (SVOM), Edition 1	Airspace user	

COMS-B2/1	PBCS approved CPDLC (B2) for domestic and Technology procedural airspace
☐ Sixth edition of the	ne GANP ②
Main Purpose 2	Provision of Air Traffic Services (ATS), with the extension of data link communications use in support of various ATM enhancements among which:
	<ul> <li>Trajectory-based operations, with new CPDLC messages to uplink route amendments (with standardized automation rules to ensure consistent Flight Management System implementation among the aircraft fleet),</li> </ul>
	<ul> <li>Surface operations, with new CPDLC TAXI (D-TAXI) messages.</li> </ul>
New Capabilities   ?	New generation of CPDLC application, named Baseline 2, designed to:
	<ul> <li>perpetuate legacy data link operations in procedural and domestic airspace,</li> <li>introduce new data link services (e.g. 4D trajectory exchange, D-TAXI).</li> </ul>
Description 3	Baseline 2 data link capabilities (CPDLC and ADS-C) support provision of data communications in all operational environments e.g., continental, oceanic, and surface in support of provision of air traffic control services.
	Baseline 2 CPDLC has been designed to be independent of the underlying technologies.
	PBCS will also enhance airspace access for State aircraft as it would offer opportunities for application of performance-equivalence.
Maturity Level 2	Validation

### Human Factor Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes





ATIONS 🙍
ASBU Element
COMS-B0/1 - CPDLC (FANS 1/A & ATN B1) for domestic and procedural airspace
COMS-B1/1 - PBCS approved CPDLC (FANS 1/A+) for domestic and procedural airspace
COMI-B0/2 - Aeronautical Telecommunication Network/Open System Interconnection (ATN/OSI)
COMI-B2/1 - Air-Ground ATN/IPS

ENABLER	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Operational Communicati procedures on service	Datalink performance requirements and monitoring	Guidance to support deployment of Performance Based operations, such as: ICAO Doc 9869 Third Edition Performance-Based Communication and Surveillance (PBCS) Manual	ANSP Aircraft manufacturer	2019	
			Aircraft operator		
			Carvelliance (i 200) Manaai	Communication service provider	
Operational	Communicati	ti CPDLC (B2)	Requirements and guidance to support	ANSP	2024
procedures on service	procedures and monitoring	deployment of CPDLC operations, such as: Annex 10 Vol II ICAO Doc 4444,  Procedures for Air Navigation Services	Aircraft manufacturer		
			Aircraft operator		
			Air Traffic Management ICAO Doc 10037 Edition 2 Global Operational Datalink Manual (GOLD)		

Airborne system capability	Communicati on service	Baseline 2 CPDLC aircraft system	Technical standards to ensure operational and technical interoperability, such as: Annex 10 Vol II ED228A/DO350A, Baseline 2 Safety and Performance Requirements ED229A/DO351A, Baseline 2 Interoperability Requirements ED230A/DO352A, Baseline 2 FANS 1/A Accommodation Interoperability Requirements ED232A/DO353A, Baseline 2 ATN B1 Accommodation Interoperability Requirements	Aircraft manufacturer Aircraft operator	2016
Ground system infrastructur e	Communicati on service	Baseline 2 CPDLC Ground System	Technical standards to ensure operational and technical interoperability, such as: Annex 10 Vol II ED228A/DO350A, Baseline 2 Safety and Performance Requirements ED229A/DO351A, Baseline 2 Interoperability Requirements ED230A/DO352A, Baseline 2 FANS 1/A Accommodation Interoperability Requirements ED232A/DO353A, Baseline 2 ATN B1 Accommodation Interoperability Requirements	ANSP Ground systems supplier	2016
Training	Communicati on service	Training requirements for PBCS approved CPDLC (B2) for domestic and procedural airspace	Controllers training, Flight Crew Training, Maintenance and Flight Operations Training. ICAO Doc 10037 Edition 2 Global Operational Data link Manual (GOLD)	ANSP Aircraft manufacturer Aircraft operator	2019
Regulatory provisions	Operational Approval	PBCS Approval	Requirements and guidance for PBCS operational authorization in Annex 6 and Doc 9869, 3rd Edition	CAA Aircraft operator	2019
Regulatory provisions	SMS	CPDLC PBCS (B2) Safety Management System	Requirements to support local safety cases. References: Annex 19 Annex 11 PANS ATM 4444	ANSP	2013

# COMS-B2/2 PBCS Approved ADS-C (B2) for domestic and Technology procedural airspace

☐ Sixth edition of the GANP ②

Main Purpose Provision of Air Traffic Services (ATS), with the extension of data link communications use in support of various ATM enhancements among which:

• Trajectory-based operations, in particular with ADS-C Extended Project Profile (i.e. predicted route ahead of the aircraft, up to 128 waypoints with their predicted level, speed and time).

New Capabilities New generation of ADS-C applications, named Baseline 2, designed to:

- perpetuate legacy data link operations in procedural airspace
- new data link services (e.g.4D trajectory exchange)

Description ?

Baseline 2 data link capabilities (CPDLC and ADS-C) support provision of data communications in all operational environments e.g., continental, oceanic, and surface in support of provision of air traffic control services.

Baseline 2 ADS-C has been designed to be independent of the underlying technologies.

PBCS will also enhance airspace access for State aircraft as it would offer opportunities for application of performance-equivalence.

Maturity Level ?

Validation

**Human Factor** Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes



Tactical-Pre ops Tactical-During ops



Departure En-route Arrival

### **DEPENDENCIES AND RELATIONS 3** Type of Dependencies **ASBU Element** Evolution COMS-B1/2 - PBCS approved ADS-C (FANS 1/A+) for procedural airspace Relation-technology need COMI-B0/2 - Aeronautical Telecommunication Network/Open System Interconnection (ATN/OSI) Relation-benefit COMI-B2/1 - Air-Ground ATN/IPS

ENABLER	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Operational	Communicati	Datalink	Guidance to support deployment of	ANSP	2024
procedures	on service	performance requirements and	Performance Based operations, such as: ICAO Doc 9869 Fourth Edition	Aircraft manufacturer	
		monitoring (B2 ADS-C)	Performance-Based Communication and Surveillance (PBCS) Manual	Aircraft operator	
		AD0-0)	ourveillance (i 500) Maridai	Communication service provider	

Operational procedures	Communicati on service	ADS-C (B2) procedures and monitoring	Requirements and guidance to support deployment of CPDLC operations, such as: Annex 10 Vol II ICAO Doc 4444, Procedures for Air Navigation Services Air Traffic Management ICAO Doc 10037 Edition 2 Global Operational Datalink Manual (GOLD)	ANSP Aircraft manufacturer Aircraft operator	2024
Airborne system capability	Communicati on service	Baseline 2 ADS-C aircraft system	Technical standards to ensure operational and technical interoperability, such as: Annex 10 Vol II ED228A/DO350A, Baseline 2 Safety and Performance Requirements ED229A/DO351A, Baseline 2 Interoperability Requirements ED230A/DO352A, Baseline 2 FANS 1/A Accommodation Interoperability Requirements ED232A/DO353A, Baseline 2 ATN B1 Accommodation Interoperability Requirements	Aircraft manufacturer Aircraft operator	2016
Ground system infrastructur e	Communicati on service	Baseline 2 ADS- C Ground System	Technical standards to ensure operational and technical interoperability, such as: Annex 10 Vol II ED228A/DO350A, Baseline 2 Safety and Performance Requirements ED229A/DO351A, Baseline 2 Interoperability Requirements ED230A/DO352A, Baseline 2 FANS 1/A Accommodation Interoperability Requirements ED232A/DO353A, Baseline 2 ATN B1 Accommodation Interoperability Requirements	ANSP Ground systems supplier	2016
Training	Communicati on service	Training requirements for PBCS approved ADS-C (B2) for domestic and procedural airspace	Controllers training, Flight Crew Training, Maintenance and Flight Operations Training. ICAO Doc 10037 Edition 2 Global Operational Data link Manual (GOLD)	ANSP Aircraft manufacturer Aircraft operator	2019
Regulatory provisions	SMS	ADS-C PBCS (B2) Safety Management System	Requirements to support local safety cases. References: Annex 19 Annex 11 PANS ATM 4444	ANSP	2013
Regulatory provisions	Operational Approval	PBCS Approval (RSP 160)	Requirements and guidance for PBCS operational authorization in Annex 6 and Doc 9869, 4th Edition	CAA Aircraft operator	2024

☐ Sixth edition of the GANP ②

Main Purpose Supports introduction of reduced separation minima in procedural airspace.

New Capabilities SATVOICE systems are demonstrated compliant with a new RCP specification (to be developed).

Description 2

In procedural airspace, PBCS approved SATVOICE systems provides the controller with intervention capability, allowing when used in conjunction with other enablers (e.g. ADS-C or space-based ADS-B and navigation capabilities), reduced separation minima and thus capacity increase.

PBCS will also enhance airspace access for State aircraft as it would offer opportunities for application of performance-equivalence.

Maturity Level ?

Validation

Human Factor
Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes

### PLANNING LAYERS ②

Tactical-During ops

OPERATIONS ?

En-route

DEPENDENCIES AND RELATIONS					
Type of Dependencies	ASBU Element				
Evolution	COMS-B1/3 - SATVOICE (incl. routine communications) for procedural airspace				
Relation-technology need	COMI-B0/5 - Satellite communications (SATCOM) Class C Data				

ENABLER	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Regulatory provisions	SMS	SATVOICE PBCS SMS for procedural airspace	Requirements to support local safety cases. References: Annex 19 Annex 11 PANS ATM 4444	ANSP	2013
Operational procedures	-	SATVOICE PBCS operational procedures for procedural airspace	PANS-ATM (Doc 4444), Procedures for Air Navigation Services — Air Traffic Management Doc 10038, Satellite Voice Operations Manual (SVOM), Edition 2	ANSP Aircraft manufacturer Aircraft operator	2024

Operational procedures	-	SATVOICE PBCS performance monitoring for procedural airspace	Performance-Based Communication and Surveillance (PBCS) Manual, Edition 4	ANSP  Aircraft manufacturer  Aircraft operator  Communication service provider	2024
Airborne system capability	Aircraft system	SATVOICE PBCS airborne system for procedural airspace	Annex 10, Volume III Manual on the Aeronautical Mobile Satellite (Route) Service. (Doc 9925)	Aircraft manufacturer Aircraft operator	2024
Ground system infrastructur e	-	SATVOICE PBCS ground system for procedural airspace	Annex 10, Volume III Manual on the Aeronautical Mobile Satellite (Route) Service. (Doc 9925)	Ground systems supplier	2024
Regulatory provisions	Operational Approval	SATVOICE PBCS operational approval for procedural airspace	Requirements and guidance for PBCS operational authorization in Annex 6 and Doc 9869, 4th Edition.	CAA Aircraft operator	2024
Training	-	Training for SATVOICE PBCS for procedural airspace	Doc 10038, Satellite Voice Operations Manual (SVOM), Edition 2	ANSP Aircraft operator	2024

COMS-B3/1	Extended CPDLC (B2 incl. Adv-IM and dynamic Technology RNP) for dense and complex airspace
☐ Sixth edition of the	e GANP
Main Purpose	Supports dynamic PBN rerouting and advanced interval management operations.
New Capabilities 2	Extension of B2 CPDLC services to introduce instructions for dynamic RNP and advanced interval management.
Description 2	
Maturity Level    Output  Description:	Concept

### Human Factor Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes

### PLANNING LAYERS ②

Tactical-Pre ops Tactical-During ops

### OPERATIONS ?

Departure En-route Arrival

### DEPENDENCIES AND RELATIONS 2

Type of Dependencies

**ASBU Element** 

**Evolution** 


COMS-B2/1 - PBCS approved CPDLC (B2) for domestic and procedural

airspace

### **ENABLERS**

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Operational	Communicati	CPDLC (B2 incl.	Requirements and guidance to support	ANSP	2028
procedures	on service	Adv-IM and DRNP)	deployment of CPDLC operations, such as: Annex 10 Vol II ICAO Doc 4444,	Aircraft manufacturer	
		procedures and monitoring	Procedures for Air Navigation Services Air Traffic Management ICAO Doc 10037	Aircraft operator	
		monitoring	Edition x Global Operational Data link Manual (GOLD)		
Operational	Communicati	Datalink	Guidance to support deployment of	Airport operator	2028
procedures	on service	performance	Performance Based operations, such as:	ANSP	
		requirements and monitoring (B2	ICAO Doc 9869 Edition x Performance- Based Communication and Surveillance	Aircraft manufacturer	
		incl. Adv-IM and DRNP)	(PBCS) Manual	Communication service provider	
Airborne	Communicati	Baseline 2	Technical standards to ensure operational	Aircraft manufacturer	2023
system capability	on service	CPDLC (B2 incl. Adv-IM and	and technical interoperability, such as: Annex 10 Vol II ED228B/DO350B,	Aircraft operator	
		DRNP) aircraft	Baseline 2 Safety and Performance		
		system	Requirements ED229B/DO351B,		
			Baseline 2 Interoperability Requirements ED230B/DO352B, Baseline 2 FANS 1/A		
			Accommodation Interoperability		
			Requirements ED232B/DO353B,		
			Baseline 2 ATN B1 Accommodation		
			Interoperability Requirements		

system on service CPDLC (B2 incl. and technical interoperability, such as: Adv-IM and Annex 10 Vol II ED228B/DO350B, DRNP) Ground Baseline 2 Safety and Performance System Requirements ED229B/DO351B, Baseline 2 Interoperability Requirements ED230B/DO352B, Baseline 2 FANS 1/A Accommodation Interoperability Requirements ED232B/DO353B, Baseline 2 ATN B1 Accommodation Interoperability Requirements						
on service requirements for extended CPDLC (B2 incl. Adv-IM and DRNP) for domestic airspace  Regulatory provisions  Regulatory Operational PBCS Approval Provisions  Regulatory Provisions  Regulatory Operational PBCS Approval Provisions Approval PDC (B2 incl. Adv-IM and Doc 9869, X Edition  Requirements and Flight Operations  Training. ICAO Doc 10037 Edition X  Global Operational Pata link Manual (GOLD)  Aircraft operator  Aircraft operator  Aircraft operator  Aircraft operator  Aircraft operator  Aircraft operator	Ground system infrastructur e		CPDLC (B2 incl. Adv-IM and DRNP) Ground	and technical interoperability, such as: Annex 10 Vol II ED228B/DO350B, Baseline 2 Safety and Performance Requirements ED229B/DO351B, Baseline 2 Interoperability Requirements ED230B/DO352B, Baseline 2 FANS 1/A Accommodation Interoperability Requirements ED232B/DO353B, Baseline 2 ATN B1 Accommodation	Ground systems	2023
provisions  (B2 incl. Adv-IM and DRNP) Cases. References: Annex 19 Annex 11 PANS ATM 4444  Safety Management System  Regulatory Operational PBCS Approval Provisions Approval CPDLC (B2 incl. Adv-IM and Doc 9869, X Edition  Cases. References: Annex 19 Annex 11  PANS ATM 4444  PANS ATM 4444  Requirements and guidance for PBCS Operational authorization in Annex 6 and Doc 9869, X Edition	Training		requirements for extended CPDLC (B2 incl. Adv-IM and DRNP) for domestic	Maintenance and Flight Operations Training. ICAO Doc 10037 Edition x Global Operational Data link Manual	Aircraft manufacturer Aircraft	2025
provisions Approval CPDLC (B2 incl. operational authorization in Annex 6 and Aircraft operator	-	SMS	(B2 incl. Adv-IM and DRNP) Safety Management	cases. References: Annex 19 Annex 11	ANSP	2013
		·	CPDLC (B2 incl. Adv-IM and	operational authorization in Annex 6 and	Aircraft	2028



### Human Factor Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes

### PLANNING LAYERS ②

Tactical-Pre ops Tactical-During ops



Departure En-route Arrival

### DEPENDENCIES AND RELATIONS ②

Type of Dependencies

**Evolution** 

COMS-B2/2 - PBCS Approved ADS-C (B2) for domestic and procedural

airspace

### FNARI FRS

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Operational procedures	Communicati on service	Datalink performance	Guidance to support deployment of Performance Based operations, such as:	Airport operator	2028
procedures	OITSEIVICE	requirements and	ICAO Doc 9869 Edition x Performance-	ANSP Aircraft	
		monitoring (B2 incl. Adv-IM and	Based Communication and Surveillance (PBCS) Manual	manufacturer  Communication	
		DRNP)		service provider	
Operational Communica		ADS-C (B2 incl.	Requirements and guidance to support	ANSP	2028
procedures	on service	Adv-IM and DRNP)	deployment of CPDLC operations, such as: Annex 10 Vol II ICAO Doc 4444,	Aircraft manufacturer	
		procedures and monitoring	Procedures for Air Navigation Services Air Traffic Management ICAO Doc 10037	Aircraft operator	
		monitoring	Edition x Global Operational Data link Manual (GOLD)		
Airborne	Communicati	Baseline 2 ADS-	Technical standards to ensure operational	Aircraft manufacturer	2023
system capability	on service	C (B2 incl. Adv- IM and DRNP)	and technical interoperability, such as: Annex 10 Vol II ED228B/DO350B,	Aircraft operator	
		aircraft system	Baseline 2 Safety and Performance Requirements ED229B/DO351B, Baseline 2 Interoperability Requirements ED230B/DO352B, Baseline 2 FANS 1/A Accommodation Interoperability Requirements ED232B/DO353B, Baseline 2 ATN B1 Accommodation Interoperability Requirements		

Ground system infrastructur e	Communicati on service	Baseline 2 ADS-C (B2 incl. Adv-IM and DRNP) Ground System	Technical standards to ensure operational and technical interoperability, such as: Annex 10 Vol II ED228B/DO350B, Baseline 2 Safety and Performance Requirements ED229B/DO351B, Baseline 2 Interoperability Requirements ED230B/DO352B, Baseline 2 FANS 1/A Accommodation Interoperability Requirements ED232B/DO353B, Baseline 2 ATN B1 Accommodation Interoperability Requirements	Ground systems supplier	2023
Training	Communicati on service	Training requirements for extended ADS-C (B2 incl. Adv-IM and DRNP) for domestic airspace	Controllers Training, Flight Crew Training, Maintenance and Flight Operations Training. ICAO Doc 10037 Edition x Global Operational Data link Manual (GOLD)	ANSP Aircraft manufacturer Aircraft operator	2025
Regulatory provisions	SMS	ADS-C PBCS (B2 incl. Adv-IM and DRNP) Safety Management System	Requirements to support local safety cases. References: Annex 19 Annex 11 PANS ATM 4444	ANSP	2013
Regulatory provisions	Operational Approval	PBCS Approval ADS-C (B2 incl. Adv-IM and DRNP)	Requirements and guidance for PBCS operational authorization in Annex 6 and Doc 9869, X Edition	CAA Aircraft operator	2028

# CSEP \_\_\_\_

# CSEP-B1/1 Basic airborne situational awareness during flight Operational operations (AIRB) Sixth edition of the GANP Main Purpose To improve traffic situational awareness in all phases of flight.

- New Capabilities AIRB facilitates out-the-window visual acquisition of airborne traffic within visual range and traffic situational awareness for traffic beyond visual range.
  - It enhances traffic situational awareness and quicker visual acquisition of targets through basic airborne situational awareness during flight operations enabled by the use of a cockpit display traffic information (CDTI).
  - It supplements the flight crew's out the window scan and radio communications listening.
  - It supports the flight crew in integrating information from these sources into a comprehensive and accurate traffic picture including long traffic detection range.
  - It also enables communication with surrounding aircraft on common/local frequency (e.g. turbulence reports, uncontrolled airfield operations).

### Description ?

The use of cockpit displays to provide the flight crew with a graphical depiction of traffic using relative range and bearing, supplemented by altitude, flight ID and other information. This element represents the use of the cockpit display traffic information (CDTI) with appropriate ADS-B data filtered for traffic situational awareness. The CDTI is capable of merging data with TCAS. It is recommended to use the display where ACAS information is already provided (if ACAS-equipped)

### Maturity Level ?

Ready for implementation

### **Human Factor** Considerations

- 1. Does it imply a change in task by a user or affected others? No
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? No

### PLANNING LAYERS ?

Tactical-During ops



### **DEPENDENCIES AND RELATIONS 3** Type of Dependencies **ASBU Element** Relation-technology need ASUR-B0/1 - Automatic Dependent Surveillance – Broadcast (ADS-B) Relation-technology benefit ACAS-B1/1 - ACAS Improvements

ENABLER	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Regulatory provisions	Certification	Certification of CDTI for airborne situational awareness	References: ICAO Annex 10 Volume IV basic technical requirements ICAO Doc 9994 ADS-B IN equipment/function compliant with DO-317B/ED194A (2015)	CAA  Aircraft manufacturer  Aircraft operator	2015
Operational procedures	Operations	SOPs for the use of CDTI for AIRB	References: PANS-OPS (Doc 8168) operation of ADS-B IN traffic display (2016) Standard Operating Procedures	Aircraft operator	2013

Airborne system capability	Surveillance	ADS-B IN equipment/function	ADS-B IN equipment/function compliant with DO-317B/ED194A (2015)	Airspace user Aircraft manufacturer	2015
Airborne system	Aircraft system	CDTI	Cockpit Display of Traffic Information (CDTI). The CDTI may be shared with	Aircraft manufacturer	2013
capability	cyclom		ACAS information traffic display but we should not assume this capability is only	operator	
			for ACAS-equipped aircraft. References:		
Training -	-	Training	The appropriate use of the traffic display	Aircraft operator	2013
		requirements for AIRB	could be evaluated during recurrent training on ACAS. The equipage of AIRB capability is unknown to ATC. The use of AIRB must remain transparent to ATC. References:		

### DEPLOYMENT APPLICABILITY

### **Operational conditions:**

AIRB may be introduced in a partial equipage of ADS-B OUT, in which only some aircraft are equipped with ADS-B OUT.

### Main intended benefits:

Туре	Operational description	Benefitting stakeholder(s)
	Safety and efficiency: Improving the flight crew's decision-making process and the resulting actions for the safe and efficient operation of the flight with earlier detection of developing unsafe situations and better flight trajectory execution. Note: NOTE: Benefits vary depending on the airspace and operational flight rules.	Airspace user
	Safety and efficiency: Identification of the traffic ahead, enabling direct pilot-to-pilot communications, in oceanic airspace, to request turbulence information. Note:  NOTE: Benefits vary depending on the airspace and operational flight rules.	Airspace user
Direct benefits	Vertical flight efficiency: Saving up to 15 000 Kg fuel per aircraft annually in North Atlantic airspace (5 min separation, about 40 NM). Substantially higher benefits in larger separation environments	Aircraft operator
	Safety: Reduced weather turbulence encounters through direct pilot-to-pilot communications Enhanced traffic situation awareness	Airspace user

Туре	Operational description	Benefitting stakeholder(s)
	Improve situational awareness of the flight crew	Airspace user
Indirect benefits	Improved efficiency, reduced exchanges of R/T.	ANSP

КРА	Focus Areas	Most specific performance objective(s) supported	KPI Impact	KPI
Safety		Improve mid-air collision avoidance (safety net)	++	KPI20: Number of aircraft accidents KPI23: Number of airprox/TCAS alert/loss of separation/near midair collisions/midair collisions (MAC)
Safety		Improve separation provision (at a planning horizon > 2 minutes)	++	KPI20: Number of aircraft accidents KPI23: Number of airprox/TCAS alert/loss of separation/near midair collisions/midair collisions (MAC)

CSEP-B1/2	Visual Separation on Approach (VSA)	Operational
☐ Sixth edition of th	e GANP 🕜	
Main Purpose    Output  Description:	To assist pilots in maintaining own separation duri is defined to support aircraft performing successive	
New Capabilities	VSA is a situational awareness capability that offer procedures described in PANS-ATM (6.5.3.4 and own separation and quicker visual acquisition of property approach procedures enabled by the use of a CD scan and radio communications listening.	6.5.3.5). It assist the flight crew in maintaining receding aircraft during successive visual

Description 
This element is used to support existing procedures, i.e., the pilot can use the traffic display to

support his visual scan of the preceding aircraft during the approach procedure if the preceding

aircraft is transmitting ADS-B OUT surveillance data.

Maturity Level ? Ready for implementation

Human Factor 1. Does it imply a change in task by a user or affected others? No

Considerations

2. Does it imply processing of new information by the user? Yes

3. Does it imply the use of new equipment? Yes

4. Does it imply a change to levels of automation? No

### PLANNING LAYERS 3

Tactical-During ops

OPERATIONS ?

Arrival

### DEPENDENCIES AND RELATIONS @

Type of Dependencies

ASBU Element

Relation-technology need

ASUR-B0/1 - Automatic Dependent Surveillance - Broadcast (ADS-B)

Relation-technology benefit

ACAS-B1/1 - ACAS Improvements

ENABLEF	RS				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Regulatory provisions	Certification	Certification of CDTI for airborne situational awareness	References: ICAO Annex 10 Volume IV basic technical requirements ICAO Doc 9994 ADS-B IN equipment/function compliant with DO-317B/ED194A (2015)	CAA Aircraft manufacturer Aircraft operator	2015
Airborne system capability	Surveillance	ADS-B IN equipment/function	ADS-B IN equipment/function compliant with DO-317B/ED194A (2015)	Airspace user Aircraft manufacturer	2015
Airborne system capability	Aircraft system	CDTI	Cockpit Display of Traffic Information (CDTI). The CDTI may be shared with ACAS information traffic display but we should not assume this capability is only for ACAS-equipped aircraft. References:	Aircraft manufacturer Aircraft operator	2013
Training	-	Training requirements for VSA	Training should be developed and given for the system functions, indications and interactions for each application/capability. The equipage of ADS-B IN is unknown to ATC. The use of	Aircraft operator	2013

ATC.

ADS-B IN must remain transparent to

Operational procedures	Operations	SOPs for the use of CDTI for VSA	References: ICAO Doc 8168 - PANS- OPS; operation of ADS-B IN traffic display (2016)	Aircraft operator	2016
Airborne system capability	Surveillance	ADS-B OUT equipment/functi	ADS-B OUT capability required for the reference aircraft	Aircraft operator	2015

### **DEPLOYMENT APPLICABILITY**

### **Operational conditions:**

The application can be used by all suitably equipped aircraft during approach to any airports where own separation is used. VSA may be introduced in a partial equipage of ADS-B OUT environment, in which only some aircraft are equipped with ADS-B OUT. VSA is applicable for all types of runway configurations where successive visual approaches are in use (PANS-ATM 6.5.3).

### Main intended benefits:

Туре	Operational description	Benefitting stakeholder(s)
Direct benefits	VSA improve the efficiency and safety of arrival traffic at airports.	Airport operator ANSP
	The safety of the operation will be improved through the provision of accurate data to the pilots (e.g. preceding traffic ground speed) allowing them to better predict the evolution of the traffic.	Airport operator
	Improve situational awareness of the flight crew	Aircraft operator

КРА	Focus Areas	Most specific performance objective(s) supported	KPI Impact	KPI
Safety		Improve separation provision (at a planning horizon > 2 minutes)	++	KPI20: Number of aircraft accidents KPI23: Number of airprox/TCAS alert/loss of separation/near midair collisions/midair collisions (MAC)

1/3	Performance Based Longitudinal Separation	Operational
	Minima	

☐ Sixth edition of the GANP ②

CSEP-B

Main Purpose <a> Reduced separation allowing more flights to operate in their optimum flight levels.</a>

New Capabilities The ability of aircraft to accurately navigate along a specified path and the ability to provide via data communication the position, intent and current navigation performance of the aircraft allow flights to

be cleared to fly at reduced longitudinal separations.

Description 50 NM, 30 NM and 5 minutes longitudinal separation have been made conditional on Required Communication Performance 240 (RCP 240) and Required Surveillance Performance 180 (RSP

180). Application of the separation may also require an RNP approval.

(Table to be inserted)

Human Factor
Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes

### PLANNING LAYERS ?

Tactical-During ops

OPERATIONS ?

En-route

DEPENDENCIES AND RELATIONS 2					
Type of Dependencies	ASBU Element				
Relation-technology option	COMFB0/3 - VHF Data Link (VDL) Mode 0/A				
Relation-technology option	COMFB0/4 - VHF Data Link (VDL) Mode 2 Basic				
Relation-technology option	COMS-B0/1 - CPDLC (FANS 1/A & ATN B1) for domestic and procedural airspace				
Relation-technology option	COMS-B1/1 - PBCS approved CPDLC (FANS 1/A+) for domestic and procedural airspace				
Relation-technology option	COMS-B0/2 - ADS-C (FANS 1/A) for procedural airspace				
Relation-technology option	COMS-B1/2 - PBCS approved ADS-C (FANS 1/A+) for procedural airspace				
Relation-technology option	NAVS-B0/3 - Aircraft Based Augmentation Systems (ABAS)				

### **ENABLERS**

Enabler Type Enabler Name Description / References Stakeholders Year

Regulatory provisions	Operational Approval	Operational Approval for performance- based longitudinal separation	PBN, PBCS (when required)	CAA	2019
Operational procedures	Design and operations	Procedures for PBLoSM	Design and use of operational procedures shall be designed and used for the application of reduced longitudinal separation minima Reference: ICAO PBN, PBCS and GOLD manual	ANSP	2019
Ground system infrastructur e	Surveillance	Surveillance systems for PBLoSM	To support RSP 180	ANSP	2019
Ground system infrastructur e	Navigation	Navigation systems for PBLoSM	To support RNP 2, 4 or 10	ANSP	2019
Ground system infrastructur e	Communicati	Communication systems for PBLoSM	To support RCP 240	ANSP	2019
Training	-	Training requirements for PBLoSM	ATCO Training and Flight Crew Training Train for PBN Reduced Longitudinal Separation Minima Provide training to staff prior to implementation	ANSP Aircraft operator	2019
Airborne system capability	Communicati on service	Communication capabilities for PBLoSM	Aircraft and crew approvals for appropriate RNP specifications Reference: Aircraft and crew approvals for RCP 240 and ADS-C/CPDLC	Aircraft manufacturer Aircraft operator	2019
Airborne system capability	Navigation	Navigation capabilities for PBLoSM	Aircraft and crew approvals for appropriate RNP specifications	Aircraft manufacturer Aircraft operator	2019
Airborne system capability	Surveillance	Surveillance capabilities for PBLoSM	Aircraft and crew approvals for appropriate RNP specifications Reference: Aircraft and crew approvals for RSP 180	Aircraft manufacturer Aircraft operator	2019

# DEPLOYMENT APPLICABILITY

### Operational conditions:

Applicable to oceanic airspace and/or remote areas.

### Main intended benefits:

### INTENDED PERFORMANCE IMPACT ON SPECIFIC KPAS AND KPIS

KPA	Focus Areas	Most specific performance objective(s) supported	KPI Impact	КРІ
Capacity	Capacity, throughput & utilization	Improve what's needed to reduce longitudinal separation minima	++	KPI06: En-route airspace capacity
Capacity	Capacity, throughput & utilization	Take advantage of increased navigation precision (airspace with PBN operations) to implement route networks and airspace structures with smaller lateral and vertical safety buffers	++	KPI06: En-route airspace capacity

### CSEP-B1/4 Performance Based Lateral Separation Minima Operational

☐ Sixth edition of the GANP ②

Main Purpose To increase airspace capacity and allow optimum utilization of available airspace.

New Capabilities The ability of aircraft to accurately navigate along a specified path and the ability to provide via data communication the position, intent and current navigation performance of the aircraft allow flights to be cleared to fly at reduced lateral separations.

Description This element describes the application of lateral separation of 23 NM between any combination of RNP 4 and RNP 2 approved aircraft operating on parallel or non-intersecting tracks.

Maturity Level Standardization

Human Factor Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes

### PLANNING LAYERS ?

Tactical-During ops

OPERATIONS ?

En-route

### DEPENDENCIES AND RELATIONS 3

Type of Dependencies ASBU Element

Relation-technology option COMI-B0/3 - VHF Data Link (VDL) Mode 0/A

Relation-technology option	COMFB0/4 - VHF Data Link (VDL) Mode 2 Basic
Relation-technology option	COMS-B0/1 - CPDLC (FANS 1/A & ATN B1) for domestic and procedural airspace
Relation-technology option	COMS-B1/1 - PBCS approved CPDLC (FANS 1/A+) for domestic and procedural airspace
Relation-technology option	COMS-B0/2 - ADS-C (FANS 1/A) for procedural airspace
Relation-technology option	COMS-B1/2 - PBCS approved ADS-C (FANS 1/A+) for procedural airspace
Relation-technology option	NAVS-B0/3 - Aircraft Based Augmentation Systems (ABAS)

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Regulatory provisions	Operational Approval	Operational Approval for performance- based lateral separation	Approval of PBN, PBCS	CAA	2019
Operational procedures	Design and operations	Procedures for PBLaSM	Design and use of operational procedures for the application of reduced lateral separation minima Reference: ICAO PBN, PBCS and GOLD manual	ANSP	2019
Training	-	Training requirements for PBLaSM	ATCO training ATCO and Flight Crew training Performance Based Lateral Separation Minima Provide training to staff prior to implementation	ANSP Aircraft operator	2019
Airborne system capability	Communicati on service	Communication capabilities for PBLaSM	Aircraft and crew approvals for RCP 240	Aircraft manufacturer Aircraft operator	2019
Airborne system capability	Navigation	Navigation capabilities for PBLaSM	Aircraft and crew approvals for appropriate RNP specifications	Aircraft manufacturer Aircraft operator	2019
Airborne system capability	Surveillance	Surveillance capabilities for PBLaSM	Aircraft and crew approvals for RSP 180	Aircraft manufacturer Aircraft operator	2019
Ground system infrastructur	Communicati ons	Communication systems for PBLaSM	To support the specified RCP	ANSP	2019

Ground system infrastructur e	Navigation	Navigation systems for PBLaSM	To support the specified RNP	ANSP	2019
Ground system infrastructur e	Surveillance	Surveillance systems for PBLaSM	To support the specified RSP	ANSP	2019

### **DEPLOYMENT APPLICABILITY**

**Operational conditions:** 

Main intended benefits:

Type Operational description Benefitting stakeholder(s)

КРА	Focus Areas	Most specific performance objective(s) supported	KPI Impact	КРІ
Capacity	Capacity, throughput & utilization	Improve what's needed to reduce lateral separation minima	++	KPI06: En-route airspace capacity


CSEP-B2/1	Interval Management (IM) Procedure	Operational
Sixth edition of the	e GANP ②	
Main Purpose 🕜	The objective of the IM application is to achieve are aircraft and the designated aircraft (referred as the flight deck that enables the pilot to actively manage	e reference aircraft), using the guidance on the
New Capabilities 3	This element allows management by the pilot of the airborne tools.	e assigned spacing from a reference aircraft using
Description 2	The air traffic controller chooses to use IM operations the aircraft need to be spaced closely together in a is accomplished by the air traffic controller providing assigned interval. The assigned interval can be defor identifying the reference aircraft (designated by clearance. While some IM clearances will keep the speed management, other clearances may include shortening.	an orderly manner or their timing synchronized. This and a clearance to the IM aircraft which includes the effined in time or distance. The pilot is responsible to the air traffic controller) and to implement the IM aircraft on its current route and result only in
Maturity Level 2	Standardization	

### Human Factor Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes

### PLANNING LAYERS 2

Tactical-During ops



DEPENDENCIES AND RELATIONS 2				
Type of Dependencies	ASBU Element			
Relation-technology need	ASUR-B0/1 - Automatic Dependent Surveillance – Broadcast (ADS-B)			
Relation-technology benefit	ACAS-B1/1 - ACAS Improvements			
Relation-benefit	ASUR-B2/1 - Evolution of ADS-B and Mode S			

Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Operational procedures	Operations	Procedures for the use of IM	PANS-ATM/PANS-OPS Interval Management Procedure (To be developed)	ANSP Aircraft operator	2025
Airborne system capability	Surveillance	Surveillance system capabilities for IM	ADS-B IN equipment/function compliant with DO-317B/ED194A (and subsequent versions) (2014) + ADS-B OUT capability required for the reference aircraft	Aircraft manufacturer Aircraft operator	2014
Airborne system capability	Navigation	Navigation system capabilities for IM	FIM equipment /spacing functions with advisories	Aircraft operator	2019
Airborne system capability	Aircraft system	Traffic display for IM	Cockpit display of traffic information	Aircraft manufacturer Aircraft operator	2019
Training	-	Training requirements for IM	Air traffic controllers, Pilots	ANSP Aircraft operator	2019
Ground system infrastructur e	ATC systems	ATC tool for IM	Ground tools/capabilities that assist the air traffic controller in issuing ATC clearances to merge and space aircraft safely and efficiently by allowing ATC to use IM clearances	ANSP	2019

Regulatory	Certification	IM Certification	ICAO Annex 10 Technical requirements	CAA	2025
provisions			(to be developed) ICAO DOC9994	Aircraft manufacturer	

Aircraft operator

### **DEPLOYMENT APPLICABILITY**

### **Operational conditions:**

The air traffic controller chooses to use IM operations to manage the interval between aircraft when the aircraft need to be spaced closely together in an orderly manner or their timing synchronized. This is accomplished by the air traffic controller providing a clearance to the IM aircraft which includes the assigned interval. The assigned interval can be defined in time or distance. The pilot is responsible for identifying the reference aircraft (designated by the air traffic controller) and to implement the IM clearance. While some IM clearances will keep the IM aircraft on its current route and result only in speed management, other clearances may include a controller-defined path lengthening or shortening Note. — IM may not work in all conditions. A combination of air traffic controller judgment and ATC automation will be needed to determine the conditions of which IM can be completed successfully. The assigned interval can be defined in time or distance.

### Main intended benefits:

Туре	Operational description	Benefitting stakeholder(s)
	The precise management of intervals between aircraft with common or merging trajectories, maximizes airspace throughput while reducing ATC workload along with more efficient aircraft fuel burn reducing environmental impact.	Airport operator ANSP
	Punctuality: IM will improve consistent spacing precision by making more frequent trajectory adjustments than is possible with a ground system alone.	ANSP Aircraft operator
	Reduction flight time variability	ANSP Aircraft operator
Direct benefits	Potential benefits of IM operations include: a) Timely speed advisories removing later requirement for path-lengthening; b) Consistent and low variance spacing between paired aircraft (e.g. at the entry to an arrival procedure and on final approach). More precise spacing can allow for higher throughput and more efficient aircraft operations; c) Optimized descent profile in high density environments; d) Reduced ATC instructions due to the reduced number of speed instructions; and e) More efficient aircraft operations for FIM-equipped aircraft, when aircraft are pre-sequenced, e.g. with the use of an arrival manager (AMAN).	ANSP Aircraft operator

Туре	Operational description	Benefitting stakeholder(s)
	Improve situational awareness of the flight crew	Aircraft operator
Indirect benefits	Reduction of radar vectoring (and of R/T exchanges between ATCO and FC).	ANSP

KPA	Focus Areas	Most specific performance objective(s) supported	KPI Impact	KPI
Capacity	Capacity, throughput & utilization	Reduce ATCO workload (enroute)	++	KPI06: En-route airspace capacity
Capacity	Capacity, throughput & utilization	Resolve ATC staffing, workload, frequency congestion problems	++	KPI10: Airport peak throughput
				KPI20: Number of

Improve separation provision (at

a planning horizon > 2 minutes)

aircraft accidents KPI23: Number of airprox/TCAS

alert/loss of

midair

separation/near

collisions/midair collisions (MAC)

INTENDED PERFORMANCE IMPACT ON SPECIFIC KPAS AND KPIS


Safety

CSEP-B2/2	Cooperative separation at low altitudes Operational
Sixth edition of the	e GANP ②
Main Purpose 2	To maintain own separation with respect to manned aviation and other UAS in the UTM airspace.
New Capabilities   Output  Description:	A dedicated function to support separation assurance is provided to the UAS, which is supported by detection capability as well as a guidance to remain well clear of any other UAS. Note: in the UTM, this function may be automated and not operated by a remote pilot.
Description 2	The UAS is capable of building a traffic picture associated to a separation assurance functionality enabling to establish and maintain the required separation from any other vehicle aka "remain well clear" using ADS-B IN for manned aviation and broadcast technologies to be determined for UAS to UAS.
Maturity Level    Output  Description:	Validation

### Human Factor Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes

# PLANNING LAYERS Tactical-During ops



DEPENDENCIES AND RELA	ATIONS O
Type of Dependencies	ASBU Element
Relation-technology need	CSEP-B1/1 - Basic airborne situational awareness during flight operations (AIRB)
Relation-technology need	ASUR-B2/2 - New community based surveillance system for airborne aircraft (low and higher airspace)

ENABLER	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Regulatory provisions	Certification	Low-altitude UAS separation certification	TBD	CAA UAS operator	2025
Regulatory provisions	Operational Approval	Low-altitude UAS separation operational approval	TBD	UAS operator	2025
Operational procedures	-	UTM rules for separation	TBC: in UTM, rules need to be established such as "remain well clear" definition, performance requirements	UAS operator	2025
Airborne system capability	Surveillance	UAS airborne surveillance	ADS-B IN 1090ES (to be clear of manned aviation) and UAT	UAS operator UAS manufacturer	2025
Ground system infrastructur e	-	Display for UTM	N/A for UAS UTM service provider and/or Remote Pilot Ground station	UAS operator UTM operator	2025
Ground system infrastructur e	Surveillance	UAT for UAS	No new requirements (maybe UAT for UAS will trigger the need for ADS-R or TIS-R ground infrastructure?	UAS operator	2025

### **DEPLOYMENT APPLICABILITY**

### **Operational conditions:**

At low altitudes.

### Main intended benefits:

**Type** 

**Operational description** 

Benefitting stakeholder(s)

### INTENDED PERFORMANCE IMPACT ON SPECIFIC KPAS AND KPIS

КРА	Focus Areas	Most specific performance objective(s) supported	KPI Impact	KPI
Safety		Maintain or improve safety of very low-level operations	++	

### CSEP-B2/3 Cooperative separation at higher airspace Operational

☐ Sixth edition of the GANP ②

To maintain own separation with respect to manned aviation and other UAS in the upper airspace. Main Purpose ?

New Capabilities A dedicated function to support separation assurance is provided to the UAS, which is supported by detection capability as well as a guidance to remain well clear of any other UAS. Note: in the UTM,

this function may be automated and not operated by a remote pilot.

Description ? The UAS is capable of building a traffic picture associated to a separation assurance functionality enabling to establish and maintain the required separation from any other vehicle aka "remain well

clear" using ADS-B IN for manned aviation and broadcast technologies to be determined for UAS

to UAS.

Maturity Level ? Validation

**Human Factor** Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes

### PLANNING LAYERS ?

Tactical-During ops

### OPERATIONS ?

Departure En-route Arrival

### **DEPENDENCIES AND RELATIONS 3**

Type of Dependencies **ASBU Element** 

Relation-technology need CSEP-B1/1 - Basic airborne situational awareness during flight operations

(AIRB)

ENABLER	S				
Enabler Category	Enabler Type	Enabler Name	Description / References	Stakeholders	Year
Regulatory provisions	Certification	Higher airspace UAS separation certification	TBD	CAA UAS operator	2025
Regulatory provisions	Operational Approval	Higher airspace UAS separation operational approval	TBD	UAS operator	2025
Operational procedures	-	Higher airspace rules for separation	In higher airspace, rules need to be established such as "remain well clear" definition, performance requirements	UAS operator	2025
Airborne system capability	Surveillance	Higher UAS airborne surveillance	ADS-B IN 1090ES (to be clear of manned aviation) and UAT	UAS operator UAS manufacturer	2025
Ground system infrastructur e	-	Display for higher UTM	N/A for UAS UTM service provider and/or Remote Pilot Ground station	UAS operator UTM operator	2025
Ground system infrastructur e	Surveillance	UAT for higher UAS	No new requirements (maybe UAT for UAS will trigger the need for ADS-R or TIS-R ground infrastructure?	UAS operator	2025
Other	-	MEL, performance compliance for higher UAS	Before reaching the higher airspace, the UAS will cross ATM airspace and may have to comply with the airspace requirements in terms of MEL, performance, It is possible that in transition period, such operations will be conducted in temporarily segregated airspace to ensure safe and limited impact on ATM operations.	UAS operator	2025

### **DEPLOYMENT APPLICABILITY**

### **Operational conditions:**

At higher airspace.

### Main intended benefits:

Type Operational description Benefitting stakeholder(s
--

### Most specific performance **KPI KPA Focus Areas KPI** objective(s) supported **Impact** Maintain or improve safety of Safety ++ higher airspace operations

CSEP-B3/1

Interval Management (IM) Procedure with complex Operational geometries

INTENDED PERFORMANCE IMPACT ON SPECIFIC KPAS AND KPIS

☐ Sixth edition of the GANP ②

Main Purpose ?

The objective of the IM application is to achieve and/or maintain an assigned spacing between one aircraft and the designated aircraft (referred as the reference aircraft), using the guidance on the flight deck that enables the pilot to actively manage the spacing relative to the reference aircraft supported by data link to facilitate exchange of complex clearances in a diversity of operational environments.

New Capabilities ? This element allows management by the pilot of the assigned spacing from a reference aircraft using airborne tools and data link in a diversity of operational environments.

Description ?

The air traffic controller chooses to use IM operations to manage the interval between aircraft when the aircraft need to be spaced closely together in an orderly manner or their timing synchronized. This is accomplished by the air traffic controller providing a clearance to the IM aircraft which includes the assigned interval. The assigned interval can be defined in time or distance.

The pilot is responsible for identifying the reference aircraft (designated by the air traffic controller) and to implement the IM clearance. While some IM clearances will keep the IM aircraft on its current route and result only in speed management, other clearances may include a controller-defined path lengthening or shortening.

Maturity Level ? Concept

**Human Factor** Considerations

- 1. Does it imply a change in task by a user or affected others? Yes
- 2. Does it imply processing of new information by the user? Yes
- 3. Does it imply the use of new equipment? Yes
- 4. Does it imply a change to levels of automation? Yes

PLANNING LAYERS ?

Tactical-During ops

**OPERATIONS ?** 

Departure En-route Arrival

DEPENDENCIES AND RELATIONS @

Type of Dependencies

**ASBU Element** 

Relation-technology need	ASUR-B2/1 - Evolution of ADS-B and Mode S
Relation-technology need	COMS-B3/1 - Extended CPDLC (B2 incl. Adv-IM and dynamic RNP) for dense and complex airspace
Evolution	CSEP-B2/1 - Interval Management (IM) Procedure

### **ENABLERS**

There are currently no enablers.

### **DEPLOYMENT APPLICABILITY**

### **Operational conditions:**

Same as in Block 2 but, this element is also applicable in environments with complex geometries.

### Main intended benefits:

Type Operational description Benefitting stakeholder(s)

KPA	Focus Areas	Most specific performance objective(s) supported	KPI Impact	KPI
Capacity	Capacity, throughput & utilization	Reduce ATCO workload (enroute)	++	KPI06: En-route airspace capacity
Capacity	Capacity, throughput & utilization	Resolve ATC staffing, workload, frequency congestion problems	++	KPI10: Airport peak throughput
Safety		Improve separation provision (at a planning horizon > 2 minutes)	++	KPI20: Number of aircraft accidents KPI23: Number of airprox/TCAS alert/loss of separation/near midair collisions/midair collisions (MAC)

CSEP-B3/2	Remain Well Clear (RWC) functionality for Operational UAS/RPAS
☐ Sixth edition of t	he GANP ②
Main Purpose 2	Aims at maintaining own separation with respect to any manned and/or unmanned aircraft in all phases of flight.

New Capabilities "Remain well clear" is a dedicated function to support separation assurance is provided to the aircraft, which must remain independent of the collision avoidance logic (ACAS).

While the detection capability can be the same, the objective of the function is different and must be supported by a specific logic based on separation minima developed to suit the new operations.

Description ?

The remote pilot ensures separation from suitably equipped aircraft (manned and/or unmanned) thanks to a traffic picture (CDTI) associated to a separation assurance functionality enabling to establish and maintain the required separation (remain well clear) in all phases of flight.

Validation

Human Factor
Considerations

### PLANNING LAYERS 3

Tactical-During ops

### OPERATIONS ?

Departure En-route Arrival

### **DEPENDENCIES AND RELATIONS 3**

DEL ENDERVOIES / IND NEED INTONS				
Type of Dependencies	ASBU Element			
Relation-technology need	ASUR-B2/1 - Evolution of ADS-B and Mode S			
Relation-operational need	ACAS-B2/2 - New collision avoidance capability as part of an overall detect and avoid system for RPAS			

### **ENABLERS**

There are currently no enablers.

### **DEPLOYMENT APPLICABILITY**

**Operational conditions:** 

Main intended benefits:

Type Operational description Benefitting stakeholder(s)

КРА	Focus Areas	Most specific performance objective(s) supported	KPI Impact	КРІ
Capacity	Capacity, throughput & utilization	Reduce ATCO workload (enroute)	++	KPI06: En-route airspace capacity
Capacity	Capacity, throughput & utilization	Resolve ATC staffing, workload, frequency congestion problems	++	KPI10: Airport peak throughput

КРА	Focus Areas	Most specific performance objective(s) supported	KPI Impact	KPI
Safety		Improve separation provision (at a planning horizon > 2 minutes)	++	KPI20: Number of aircraft accidents KPI23: Number of airprox/TCAS alert/loss of separation/near midair collisions/midair collisions (MAC)

CSEP-B4/1	Airborne separation	Operational				
☐ Sixth edition of the GANP ②						
Main Purpose 2	Aims at maintaining own separation with respect to one aircraft via a delegation of responsibility from the ATCO to the flight crew in all phases of flight.					
New Capabilities	A dedicated function to support separation assurance is provided to the aircraft, which must remain independent of the collision avoidance logic (ACAS-Bx). While the detection capability can be the same, the objective of the function is different and must be supported by a specific logic based on airborne separation minima developed to suit the new operations.					
Description ?	Airborne Separation = temporary delegation of responsibility to the flight deck for separation provision with suitably equipped designated aircraft.					
	The flight crew ensures separation from suitably equipped designated aircraft as communicated in new clearances, which relieve the controller from the responsibility for separation between these aircraft. However, the controller retains responsibility for separation from aircraft that are not part of these clearances. The flight crew/remote pilot is provided with a traffic picture (CDTI) associated to a separation assurance functionality enabling to establish and maintain the required separation (remain well clear for RPAS).					
Maturity Level ?	Validation					
Human Factor Considerations						
PLANNING L	AYERS •	OPERATIONS 2				
Tactical-During o	ps	Departure En-route Arrival				

DEPENDENCIES AND RELATIONS 2			
Type of Dependencies	ASBU Element		
Relation-operational need	ASUR-B0/1 - Automatic Dependent Surveillance – Broadcast (ADS-B)		
Relation-technology need	ASUR-B2/1 - Evolution of ADS-B and Mode S		

### **ENABLERS**

There are currently no enablers.

### **DEPLOYMENT APPLICABILITY**

**Operational conditions:** 

Main intended benefits:

Туре	Operational description	Benefitting stakeholder(s)
Direct benefits	Improve situational awareness of the flight crew	Aircraft operator

КРА	Focus Areas	Most specific performance objective(s) supported	KPI Impact	KPI
Capacity	Capacity, throughput & utilization	Reduce ATCO workload (enroute)	++	KPI06: En-route airspace capacity
Capacity	Capacity, throughput & utilization	Resolve ATC staffing, workload, frequency congestion problems	++	KPI10: Airport peak throughput
Safety		Improve separation provision (at a planning horizon > 2 minutes)	++	KPI20: Number of aircraft accidents KPI23: Number of airprox/TCAS alert/loss of separation/near midair collisions/midair collisions (MAC)